

# Jakarta HiveMind Project Documentation

## 1. HiveMind Project

### 1.1. Reference

#### 1.1.1. HiveMind Services

In HiveMind, a service is simply an object that implements a particular interface, the *service interface*. You supply the service interface (packaged as part of a module). You supply the core implementation of the interface (in the same module, or in a different module). At runtime, HiveMind puts it all together.

HiveMind uses four service models: primitive, singleton, threaded and pooled. In the primitive and singleton models, each service will ultimately be just a single object instance. In the threaded and pooled models, there may be many instances simultaneously, one for each thread.

Unlike EJBs, there's no concept of location transparency: services are always local to the same JVM. Unlike XML-based web services, there's no concept of language transparency: services are always expressed in terms of Java interfaces. Unlike JMX or Jini, there's no concept of hot-loading of services. HiveMind is kept deliberately simple, yet still very powerful, so that your code is kept simple.

##### 1.1.1.1. Defining Services

A service definition begins with a Java interface, the service interface. Any interface will do, HiveMind doesn't care, and there's no base HiveMind interface.

A module descriptor may include [<service-point>](#) elements to define services. A module may contain any number of services.

Each [<service-point>](#) establishes an id for the service and defines the interface for the service. An example is provided later in this document.

HiveMind is responsible for supplying the service implementation as needed; in most cases,

the service implementation is an additional Java class which implements the service interface. HiveMind will instantiate the class and configure it as needed. The exact timing is determined from the service's service model:

- **primitive** : the service is constructed on first reference
- **singleton** : the service is not constructed until a method of the service interface is invoked
- **threaded** : invoking a service method constructs and binds an instance of the service to the current thread
- **pooled** : as with threaded, but service implementations are stored in a pool when unbound from a thread for future use in other threads.

Additional service models can be defined via the `hivemind.ServiceModels` configuration point.

HiveMind uses a system of *proxies* for most of the service models (all except the primitive service model, which primarily exists to bootstrap the core HiveMind services used by other services). Proxies are objects that implement the service interface and take care of details such as constructing the actual implementation of a service on the fly. These lifecycle issues are kept hidden from your code behind the proxies.

A service definition may include *service contributions*, or may leave that for another module.

Ultimately, a service will consist of a core implementation (a Java object that implements the service interface) and, optionally, any number of interceptors. Interceptors sit between the core implementation and the client, and add functionality to the core implementation such as logging, security, transaction demarkation or performance monitoring. Interceptors are yet more objects that implement the service interface.

Instantiating the core service implementation, configuring it, and wrapping it with any interceptors is referred to as *constructing the service*. Typically, a service proxy will be created first. The first time that a service method is invoked on the proxy, the service implementation is instantiated and configured, and any interceptors for the service are created.

### 1.1.1.2. Extending Services

Any module may contribute to any service extension point. An [<implementation>](#) element contains these contributions. Contributions take three forms:

- Service constructors:
  - [<create-instance>](#) to instantiate an instance of a Java class as the implementation
  - [<invoke-factory>](#) to have another service create the implementation
- [<interceptor>](#) to add additional logic to a core implementation

## **Service Constructors**

A service constructor is used to instantiate a Java class as the core implementation instance for the service.

There are two forms of service constructors: instance creators and implementation factories.

An instance creator is represented by a [<create-instance>](#) element. It includes a class attribute, the Java class to instantiate.

An implementation factory is represented by a [<invoke-factory>](#) element. It includes a service-id attribute, the id of a service implementation factory service (which implements the [ServiceImplementationFactory](#) interface). The most common example is the [hivemind.BuilderFactory](#) service.

## **Implementation Factories**

An implementation factory is used to create a core implementation for a service at runtime.

Often, the factory will need some additional configuration information. For example, the [hivemind.lib.EJBProxyFactory](#) service uses its parameters to identify the JNDI name of the EJB's home interface, as well as the home interface class itself.

Parameters to factory services are the XML elements enclosed by the `<invoke-factory>` element. Much like a configuration contribution, these parameters are converted from XML into Java objects before being provided to the factory.

The most common service factory is [hivemind.BuilderFactory](#). It is used to construct a service and then set properties of the service implementation object.

## **Interceptor Contributions**

An interceptor contribution is represented by an [<interceptor>](#) element. The service-id attribute identifies a service interceptor factory service: a service that implements the [ServiceInterceptorFactory](#) interface.

An interceptor factory knows how to create an object that implements an arbitrary interface (the interface being defined by the service extension point), adding new functionality. For example, the [hivemind.LoggingInterceptor](#) factory creates an instance that logs entry and exit to each method.

The factory shouldn't care what the service interface itself is ... it should adapt to whatever interface is defined by the service extension point it will create an instance for.

A service extension point may have any number of interceptor contributions. If the order in which interceptors are applied is important, then the optional `before` and `after` attributes can be specified.

### A Stack of Interceptors

In this example, it was desired that any method logging occur first, before the other interceptors. This ensures that the time taken to log method entry and exit is not included in the performance statistics (gathered by the performance interceptor). To ensure that the logging interceptor is the first, or earliest, interceptor, the special value `*` (rather than a list of interceptor service ids) is given for its `before` attribute (within the `<interceptor>` element). This forces the logging interceptor to the front of the list (however, only a single interceptor may be so designated).

Likewise, the security checks should occur last, after logging and after performance; this is accomplished by setting the `after` attribute to `*`. The performance interceptor naturally falls between the two.

This is about as complex as an interceptor stack is likely to grow. However, through the use of explicit dependencies, almost any arrangement of interceptors is possible ... even when different modules contribute the interceptors.

Interceptors implement the `toString()` method to provide a useful identification for the interceptor, for example:

```
<Interceptor:                hivemind.LoggingInterceptor                for  
com.myco.MyService(com.myco.MyServiceInterface)>
```

This string identifies the interceptor service factory (`hivemind.LoggingInterceptor`), the service extension point (`com.myco.MyService`) and the service interface (`com.myco.MyServiceInterface`).

**Note:**

If `toString()` is part of the service interface (really, a very rare case), then the interceptor *does not* override the service implementation's method. However, this is not a recommended practice.

#### 1.1.1.3. A short example

As an example, let's create an interface with a single method, used to add together two numbers.

```
package com.myco.mypackage;  
  
public interface Adder  
{
```

```
    public int add(int arg1, int arg2);  
}
```

We could define many methods, and the methods could throw exceptions. Once more, HiveMind doesn't care.

We need to create a module to contain this service. We'll create a simple HiveMind deployment descriptor. This is an XML file, named `hivemodule.xml`, that must be included in the module's META-INF directory.

```
<?xml version="1.0"?>  
<module id="com.myco.mypackage" version="1.0.0">  
  <service-point id="Adder" interface="com.myco.mypackage.Adder"/>  
</module>
```

The complete id for this service is `com.myco.mypackage.Adder`, formed from the module id and the service id. Commonly, the service id will exactly match the complete name of the service interface, but this is not required.

Normally, the `<service-point>` would contain a [<create-instance>](#) or [<invoke-factory>](#) element, used to create the core implementation. For this example, we'll create a second module that provides the implementation. First we'll define the implementation class.

```
package com.myco.mypackage.impl;  
  
import com.myco.mypackage.Adder;  
  
public class AdderImpl implements Adder  
{  
    public int add(int arg1, int arg2)  
    {  
        return arg1 + arg2;  
    }  
}
```

That's what we meant by a POJO. We'll create a second module to provide this implementation.

```
<?xml version="1.0"?>  
<module id="com.myco.mypackage.impl" version="1.0.0">  
  <implementation service-id="com.myco.mypackage.Adder">  
    <create-instance class="com.myco.mypackage.impl.AdderImpl"/>  
  </implementation>  
</module>
```

The runtime code to access the service is very streamlined:

```
Registry registry = . . .  
Adder service = (Adder) registry.getService("com.myco.mypackage.Adder", Adder.class);  
int sum = service.add(4, 7);
```

Another module may provide an interceptor:

```
<?xml version="1.0"?>
<module id="com.myco.anotherpackage version="1.0.0">
  <implementation service-id="com.myco.mypackage.Adder">
    <interceptor service-id="hivemind.LoggingInterceptor">
  </implementation>
</module>
```

Here the Logging interceptor is applied to the service extension point. The interceptor will be inserted between the client code and the core implementation. The client in the code example won't get an instance of the `AdderImpl` class, it will get an instance of the interceptor, which internally invokes methods on the `AdderImpl` instance. Because we code against interfaces instead of implementations, the client code neither knows nor cares about this.

#### 1.1.1.4. Primitive Service Model

The simplest service model is the **primitive** service model; in this model the service is constructed on first reference. This is appropriate for services such as service factories and interceptor factories, and for several of the basic services provided in the [hivemind module](#).

#### 1.1.1.5. Singleton Service Model

Constructing a service can be somewhat expensive; it involves instantiating a core service implementation, configuring its properties (some of which may also be services), and building the stack of interceptors for the service. Although HiveMind encourages you to define your application in terms of a large number of small, simple, testable services, it is also desirable to avoid a cascade of unnecessary object creation due to the dependencies between services.

To resolve this, HiveMind defers the actual creation of services by default. This is controlled by the `model` attribute of the [<service-point>](#) element; the default model is **singleton**.

When a service is first requested a *proxy* for the service is created. This proxy implements the same service interface as the actual service and, the first time a method of the service interface is invoked, will force the construction of the actual service (with the core service implementation, interceptors, references to other services, and so forth).

In certain cases (including many of the fundamental services provided by HiveMind) this behavior is not desired; in those cases, the **primitive** service model is specified. In addition, there is rarely a need to defer service implementation or service interceptor factory services.

#### 1.1.1.6. Threaded Service Model

In general, singleton services (using the singleton or primitive service models) should be sufficient. In some cases, the service may need to keep some specific state. State and multithreading don't mix, so the **threaded** service model constructs, as needed, a service instance for the current thread. Once constructed, the service instance stays bound to the thread until it is discarded. The particular service implementation is exclusive to the thread and is only accessible from that thread.

The threaded service model uses a special proxy class (fabricated at runtime) to support this behavior; the proxy may be shared between threads but methods invoked on the proxy are redirected to the private service implementation bound to the thread. Binding of a service implementation to a thread occurs automatically, the first time a service method is invoked.

The service instance is discarded when notified to cleanup; this is controlled by the `hivemind.ThreadEventNotifier` service. If your application has any threaded services, you are responsible for invoking the `fireThreadCleanup()` method of the service.

A core implementation may implement the [Discardable](#) interface. If so, it will receive a notification as the service instance is discarded.

HiveMind includes a [servlet filter](#) to take care creating the Registry and managing the `ThreadEventNotifier` service.

#### **1.1.1.7. Pooled Service Model**

The pooled service model is very similar to the threaded model, in that a service implementation will be exclusively bound to a particular thread (until the thread is cleaned up). Unlike the threaded model, the service is not discarded; instead it is stored into a pool for later reuse with the same or a different thread.

As with the threaded model, all of this binding and unbinding is hidden behind a dynamically fabricated proxy class.

Core service implementations may implement the [RegistryShutdownListener](#) interface to receive a callback for final cleanups (as with the singleton and deferred service models).

In addition, a service may implement the [PoolManageable](#) interface to receive callbacks specific to the pooled service. The service is notified when it is activated (bound to a thread) and deactivated (unbound from the thread and returned to the pool).

#### **1.1.1.8. Service Lifecycle**

As discussed, the service model determines when a service is instantiated. In many cases, the service needs to know when it has been created (to perform any final initializations) or when

the Registry has been shut down.

A core service implementation may also implement the [RegistryShutdownListener](#) interface. When a Registry is [shutdown](#), the `registryDidShutdown()` method is invoked on all services (and many other objects, such as proxies). The order in which these notifications occur is not defined. A service may release any resources it may hold at this time. It should not invoke methods on other service interfaces.

The threaded service model does **not** register services for Registry shutdown notification; regardless of whether the core service implementation implements the `RegistryShutdownListener` interface or not. Instead, the core service implementation should implement the [Discardable](#) interface, to be informed when a service bound to a thread is discarded.

It is preferred that, whenever possible, services use the singleton service model (the default) and not the primitive model. All the service models (except for the primitive service model) expose a **proxy** object (implementing the service interface) to client code (included other services). These proxies are aware of when the Registry is shutdown and will throw an exception when a service method is invoked on them.

#### 1.1.1.9. Services and Events

It is fairly common that some services will produce events and other services will consume events. The use of the [hivemind.BuilderFactory](#) to construct a service simplifies this, using the `<event-listener>` element. The `BuilderFactory` can register a *core service implementation* (not the service itself!) as a *listener* of events produced by some other service.

The producing service must include a matched pair of listener registration methods, i.e., both `addFooListener()` and `removeFooListener`. Note that only the *implementation class* must implement the listener interface; the service interface does not have to extend the listener interface. The core service implementation is registered directly with the producer service, bypassing any interceptors or proxies.

#### 1.1.1.10. Frequently Asked Questions

- **Why do I pass the interface class to `getService()`?**

This is to add an additional level of error checking and reporting. HiveMind knows, from the module descriptors, the interface provided by the service extension point, but it can't tell if *you* know that. By passing in the interface you'll cast the returned service to, HiveMind can verify that you won't get a `ClassCastException`. Instead, it throws an exception with more details (the service extension point id, the actual interface provided,



and the interface you passed it).

- **What if no module provides a core implementation of the service?**

HiveMind checks for a service constructor when the registry itself is assembled. If a service extension point has no service constructor, an error is logged (identifying the extension point id). In addition, `getService()` will throw an `ApplicationRuntimeException`.

- **What if I need to do some initializations in my service?**

If you have additional initializations that can't occur inside your core service implementations constructor (for instance, if the initializations are based on properties set after the service implementation object is instantiated), then your class should use the [hivemind.BuilderFactory](#) to invoke an initializer method.

- **What if I don't invoke `Registry.cleanupThread()`?**

Then service implementations bound to the current thread stay bound. When the thread is next used to process a request, the same services, in whatever state they were left in, will be used. This may not be desirable in a servlet or Tapestry application, as some state from a client may be left inside the services, and a different client may be associated with the thread in later executions.

- **What if I want my service to be created early, not just when needed?**

Contribute your service into the [hivemind.EagerLoad](#) configuration; this will force HiveMind to instantiate the service on startup. This is often used when developing an application, so that configuration errors are caught early; it may also be useful when a service should be instantiated to listen for events from some other service.

### 1.1.2. Configuration Points

A central concept in HiveMind is *configuration extension points*. Once you have a set of services, its natural to want to configure those services. In HiveMind, a configuration point contains an unordered list of *elements*. Each element is contributed by a module ... any module may make contributions to any configuration point.

There is no explicit connection between a service and a configuration point, though it is often the case that a service and a configuration point will be similarly named (or even identically named; services and configuration points are in separate namespaces). Any relationship between a service and an configuration point is explicit only in code ... the service may be configured with the elements of a configuration point and operate on those elements in some way.

#### 1.1.2.1. Defining a Configuration Point

A module may include [<configuration-point>](#) elements to define new configuration points. A configuration point may specify the expected, or allowed, number of contributions:

- Zero or one
- Zero or more (the default)
- At least one
- Exactly one

At runtime, the number of actual contributions is checked against the constraint and an error is reported if the number doesn't match.

### Defining the Contribution Format

A significant portion of an configuration point is the [<schema>](#) element ... this is used to define the format of contributions that may be made inside [<contribution>](#) elements. Contributions take the form of XML elements and attributes, the [<schema>](#) element identifies which elements and which attributes and provides rules that transform the contributions into Java objects.

This is very important: what gets fed into an configuration point (in the form of contributed [<contribution>](#)s) is XML. What comes out on the other side is a list of configured Java objects. Without these XML transformation rules, it would be necessary to write Java code to walk the tree of XML elements and attributes to create the Java objects; instead this is done inside the module deployment descriptor, by specifying a [<schema>](#) for the configuration point, and providing rules for processing each contributed element.

If a contribution from an [<contribution>](#) is invalid, then a runtime error is logged and the contribution is ignored. The runtime error will identify the exact location (the file, line number and column number) of the contribution so you can go fix it.

The [<schema>](#) element contains [<element>](#) elements to describe the XML elements that may be contributed. [<element>](#)s contain [<attribute>](#)s to define the attributes allowed for those elements. [<element>](#)s also contain [<rules>](#) used to convert the contributed XML into Java objects.

Here's an example from the HiveMind test suite. The Datum object has two properties: key and value.

```
<configuration-point id="Simple">
  <schema>
    <element name="datum">
      <attribute name="key" required="true"/>
      <attribute name="value" required="true"/>

      <conversion class="hivemind.test.config.impl.Datum"/>
    </element>
  </schema>
</configuration-point>
```

```
    </element>
  </schema>
</configuration-point>

<contribution configuration-id="Simple">
  <datum key="key1" value="value1"/>
  <datum key="key2" value="value2"/>
</contribution>
```

The [<conversion>](#) element creates an instance of the class, and initializes its properties from the attributes of the contributed element (the datum and its key and value attributes). For more complex data, the [<map>](#) and [<rules>](#) elements add power (and complexity).

This extra work in the module descriptor eliminates a large amount of custom Java code that would otherwise be necessary to walk the XML contributions tree and convert elements and attributes into objects and properties. Yes, you could do this in your own code ... but would you really include all the error checking that HiveMind does? Or the line-precise error reporting? Would you bother to create unit tests for all the failure conditions?

Using HiveMind allows you to write the schema and rules and know that the conversion from XML to Java objects is done uniformly, efficiently and robustly.

The end result of this mechanism is very concise, readable contributions (as shown in the `<contribution>` in the example).

In addition, it is common for multiple configuration points to share the exact same schema. By assigning an id attribute to a `<schema>` element, you may reference the same schema for multiple configuration points. For example, the [hivemind.FactoryDefaults](#) and [hivemind.ApplicationDefaults](#) configuration points use the same schema. The hivemind module deployment descriptor accomplishes this by defining a schema for one configuration point, then referencing it from another:

```
<schema id="Defaults">
  <element name="default">
    . . .
  </element>
</schema>

<configuration-point id="FactoryDefaults" schema-id="Defaults"/>
```

Like service points and configuration points, schemas may be referenced within a single module using an unqualified id, or referenced between modules using a fully qualified id (that is, prefixed with the module's id).

#### 1.1.2.2. Accessing Configuration Points

Like services, configuration points are meant to be easy to access (the only trick is getting a reference to the registry to start from).

```
Registry registry = . . . ;
List elements = registry.getConfiguration("com.myco.MyConfig");

int count = elements.size();
for (int i = 0; i < count; i++)
{
    MyElement element = (MyElement) elements.get(i);
    . . .
}
```

**Note:**

Although it is possible to access configurations via the Registry, it is often not a good idea. It is unlikely that you want the information contained in a configuration as an unordered list. A best practice is to always access the configuration through a service, which can organize and validate the data in the configuration.

The list of elements is always returned as an unmodifiable list. An empty list may be returned.

The order of the elements in the list is not defined. If order is important, you should create a new (modifiable) list from the returned list and sort it.

Note that the elements in the list are no longer the XML elements and attributes that were contributed, the rules provided in the configuration point's [<schema>](#) are used to convert the contributed XML into Java objects.

### 1.1.2.3. Lazy Loading

At application startup, all the module deployment descriptors are located and parsed and in-memory objects created. Validations (such as having the correct number of contributions) occur at this stage.

The list of elements for an configuration point is not created until the first call to `Registry.getConfiguration()` for that configuration point.

In fact, it is not created even then. When the element list for an configuration point is first accessed, what's returned is not *really* the list of elements; it's a proxy, a stand-in for the real data. The actual elements are not converted until they are actually needed, in much the same way that the creation of services is deferred.

In general, you will never know (or need to know) this; when you access the `size()` of the list or `get()` any of its elements, the conversion of contributions into Java objects will be

triggered, and those Java objects will be returned in the list.

If there are minor errors in the contribution, then you may see errors logged; if the <contribution> contributions are significantly malformed, HiveMind may be unable to recover and will throw a runtime exception.

#### **1.1.2.4. Substitution Symbols**

The information provided by HiveMind module descriptors is entirely static, but in some cases, some aspects of the configuration should be dynamic. For example, a database URL or an e-mail address may not be known until runtime (a sophisticated application may have an installer which collects this information).

HiveMind supports this notion through *substitution symbols*. These are references to values that are supplied at runtime. Substitution symbols can appear inside literal values ... both as XML attributes, and as character data inside XML elements.

Example:

```
<contribution configuration-id="com.myco.MyConfig">
  <value> dir/foo.txt </value>
  <value> ${config.dir}/${config.file} </value>
</contribution>
```

This example contributes two elements to the `com.myco.MyConfig` configuration point. The first contribution is simply the text `dir/foo.txt`. In the second contribution, the content contains substitution symbols (which use a syntax derived from the [Ant](#) build tool). Symbol substitution occurs *before* [<schema>](#) rules are executed, so the `config.dir` and `config.file` symbols will be converted to strings first, then whatever rules are in place to convert the `value` element into a Java object will be executed.

#### **Symbol Sources**

This begs the question: where do symbol values come from? The answer is application dependent. HiveMind itself defines a configuration configuration point for this purpose: [hivemind.SymbolSources](#). Contributions to this configuration point define new objects that can provide values for symbols, and identify the order in which these objects should be consulted.

If at runtime none of the configured `SymbolSources` provides a value for a given symbol then HiveMind will leave the reference to that symbol *as is*, including the surrounding `${` and `}`. Additionally an error will be logged.

#### **1.1.2.5. Frequently Asked Questions**

- **Are there any default implementations of SymbolSource?**

There is now a configuration point for setting factory defaults: [hivemind.FactoryDefaults](#). A second configuration point, for application defaults, overrides the factory defaults: [hivemind.ApplicationDefaults](#).

[SystemPropertiesSymbolSource](#) is a one-line implementation that allows access to system properties as substitution symbols. Note that this configuration is *not* loaded by default.

Additional implementations may follow in the future.

- **What's all this about schemas and rules?**

A central goal of HiveMind is to reduce code clutter. If configuration point contributions are just strings (in a .properties file) or just XML, that puts a lot of burden on the developer whose code *reads* the configuration to then massage it into useful objects. That kind of ad-hoc code is notoriously buggy; in HiveMind it is almost entirely absent. Instead, all the XML parsing occurs inside HiveMind, which uses the schema and rules to validate and convert the XML contributions into Java objects.

You can omit the schema, in which case the elements are left as XML (instances of [Element](#)) and your code is responsible for walking the elements and attributes ... but why bother? Far easier to let HiveMind do the conversions and validations.

- **How do I know if the element list is a proxy or not?**

Basically, you can't, short of performing an `instanceof` check. There isn't any need to tell the difference between the deferred proxy to the element list and the actual element list; they are both immutable and both behave identically.

### 1.1.3. HiveDoc

HiveMind includes tools for documenting a HiveMind registry ... the combined information from all modules that are deployed at runtime. At build time, all related HiveMind module deployment descriptors are parsed and the results combined into a single file. The master file (which is only used for this documentation) is then converted into a set of HTML files using XSLT. The end result is much like JavaDoc ... it's fully hyperlinked and allows you to see all services, configuration points, contributions and schemas clearly.

Incorporated into the generated documentation is user-supplied descriptions. The [<attribute>](#), [<configuration-point>](#), [<element>](#), [<module>](#), [<schema>](#) and [<service-point>](#) elements can enclose a description (as character data), i.e.:

```
<module id="mymodule" version="1.0.0">
```

```
A module for my application with my services, etc.  
</module>
```

The HiveDoc for the HiveMind framework and library is available [here](#).

**Note:**

Details on building the documentation will be coming soon.

### 1.1.4. HiveMind Module Descriptor

The purpose of the module descriptor is to provide a runtime and compile-time description of each HiveMind module in terms of service and configuration extension points and contributions to those extension points.

The descriptor is named `hivemodule.xml` and is stored in the META-INF directory of the module.

The root element of the descriptor is the [<module>](#) element.

#### 1.1.4.1. attribute

[<attribute>](#) is used to define an attribute within an [<element>](#). Inside a [<contribution>](#), only known attributes are allowed in elements; unknown attributes will be logged as an error and ignored. In addition, some attributes are required; again, errors occur if the contributed element does not provide a value for the attribute.

Attribute	Type	Required ?	Description
name	string	yes	The name of the attribute.
required	boolean	no	If true, the attribute must be provided in the contributed configuration element. The default is false.
unique	boolean	no	If true, the attribute must contain a unique value with respect to all other contributions to the same configuration point. The default is false.
translator	string	no	The <a href="#">translator</a> configuration that is

			used to convert the attribute into a useable type. By default, the attribute is treated as a single string.
--	--	--	---

#### 1.1.4.2. configuration-point

The <configuration-point> element defines a configuration extension point.

Attribute	Type	Required ?	Description
id	string	yes	The simple id of the service extension point. The fully qualified id for the extension point is created by prefixing with the module's id (and a dot).
occurs	unbounded   0..1   1   1..n   none	no	The number of contributions allowed: <ul style="list-style-type: none"> <li>• <b>unbounded</b> (default): any number</li> <li>• <b>0..1</b>: optional</li> <li>• <b>1</b>: required</li> <li>• <b>1..n</b>: at least one</li> <li>• <b>none</b>: none allowed</li> </ul> <div> <b>Note:</b>  <b>none</b> doesn't make sense for occurrences to a configuration point, but does occasionally make sense for parameters to a factory. </div>
schema-id	string	no	Used to reference a <a href="#">&lt;schema&gt;</a> (in the same module, or a different one) that defines the format of contributions into the configuration point.



			This may be omitted, in which case the extension point will contain a list of <a href="#">Element</a> .
--	--	--	---

Contains: [<schema>](#)

`<configuration-point>` only defines a configuration point, it does not supply any data into that point. The `<contribution>` element is used to provide such data.

### 1.1.4.3. contribution

The `<contribution>` element contributes elements to an existing configuration extension point.

Attribute	Type	Required ?	Description
configuration-id	string	yes	Either the id of an <a href="#">&lt;configuration-point&gt;</a> within the module, or the fully qualified id of an <code>&lt;configuration-point&gt;</code> in another module.

The content of the `<contribution>` consists of elements. These elements are converted, in accordance with the configuration point's [<schema>](#), into Java objects.

### 1.1.4.4. conversion

`<conversion>` is an alternative to [<rules>](#) that is generally simpler and more concise. An [<element>](#) should contain `<conversion>` or `<rules>` but not both.

`<conversion>` is geared towards the typical case; a straight-forward mapping of the element to an instance of a Java class, and a mapping of the element's attributes to the properties of the Java object.

Attribute	Type	Required ?	Description
class	string	yes	The fully qualified name of a Java class to instantiate.
parent-method	string	no	The name of a method of the parent object used to add the

			created object to the parent. The default, addElement, is appropriate for top-level <element>s.
--	--	--	---

Contains: [<map>](#)

Each attribute will be mapped to a property. A limited amount of name mangling occurs: if the attribute name contains dashes, they are removed, and the character following is converted to upper case. So, an attribute named "complex-attribute-name" would be mapped to a property named "complexAttributeName". Only attributes identified with a [<attribute>](#) element will be mapped, others will be ignored.

#### 1.1.4.5. create-instance

<create-instance> is used, within [<service-point>](#) and [<implementation>](#) to create the core service implementation for a service by instantiating a class. This is appropriate for simple services that require no explicit configuration.

Attribute	Type	Required ?	Description
class	class name	yes	Fully qualified class name to instantiate.
model	primitive singleton threaded   pooled	no	The model used to construct and manage the service. <b>singleton</b> is the default.

Additional service models can be defined via the hivemind.ServiceModels configuration point.

#### 1.1.4.6. element

The <element> element is used to define an element in a the [<schema>](#). <element> may also be nested within another <element>, to indicate an element that may be enclosed within another element.

Attribute	Type	Required ?	Description
name	string	yes	The name of the element.
content-translator	string	no	The <a href="#">translator</a> configuration that is used to convert the

			element's content into a useable type. By default, the content is treated as a single string.
--	--	--	---

Contains: [<attribute>](#), [<conversion>](#), [<element>](#), [<rules>](#)

Future enhancements to the HiveMind framework will include greater sophistication in defining configuration content.

#### 1.1.4.7. implementation

The [<implementation>](#) element contributes a core implementation or interceptors to a service extension point.

Attribute	Type	Required ?	Description
service-id	string	yes	The id of the service to extend; this may be a fully qualified id, or the local id of a service within the same module.

Contains: [<create-instance>](#), [<interceptor>](#), [<invoke-factory>](#)

#### 1.1.4.8. interceptor

[<interceptor>](#) contributes an interceptor factory to a service extension point. An interceptor factory is a service which implements the [ServiceInterceptorFactory](#) interface.

When the service is constructed, each invoked interceptor factory will fabricate an interceptor class to provide additional functionality for the service.

Attribute	Type	Required ?	Description
service-id	string	yes	The id of the service that will create the interceptor for the service. This may be the local id of a service defined within the same module, or a fully qualified id.
before	string	no	A list of interceptors

			whose behavior should come later in execution than this interceptor.
after	string	no	A list of interceptors whose behavior should come earlier in execution than this interceptor.

Like a service implementation factory, a service interceptor factory may need parameters. As with [<invoke-factory>](#), parameters to the interceptor factory are enclosed by the `<interceptor>` element. The service interceptor factory will decode the parameters using the schema identified by its `parameters-schema-id` attribute.

Interceptor ordering is based on dependencies; each interceptor can identify, by interceptor service id, other interceptors. Interceptors in the `before` list are deferred until after this interceptor. Likewise, this interceptor is deferred until after all interceptors in the `after` list.

**Note:**

The `after` dependencies will look familiar to anyone who has used [Ant](#) or any version of Make. `before` dependencies are simply the opposite.

The value for `before` or `after` is a list of service ids separated by commas. Service ids may be unqualified if they are within the same module. Alternately, the fixed value `*` may be used instead of a list: this indicates that the interceptor should be ordered absolutely first or absolutely last.

#### 1.1.4.9. invoke-factory

The `<invoke-factory>` element is used to provide a service implementation for a service by invoking another service, a factory service.

Attribute	Type	Required ?	Description
service-id	string	no	The id of the factory service. This may be a simple id for a service within the same module, or a fully qualified service id. The default, if not specified, is <a href="#">hivemind.BuilderFactory</a> .
model	primitive	no	The model used to

	singleton threaded   pooled		construct and manage the service. <b>singleton</b> is the default.
--	--------------------------------	--	--

A service factory defines its parameters in terms of a schema. The content of the `<invoke-factory>` is converted, in accordance with the factory's schema, and provided to the factory.

**Note:**

Additional service models can be defined via the `hivemind.ServiceModels` configuration point.

#### 1.1.4.10. map

The `<map>` element appears within [conversion](#) to override the default mapping from an attribute to a property. By default, the property name is expected to match the attribute name (with the name mangling described in the description of [conversion](#)); the `<map>` element is used to handle exceptions to the rule.

Attribute	Type	Required ?	Description
attribute	string	yes	The name of the attribute, which should match a name defined by an <a href="#">attribute</a> (of the enclosing <a href="#">element</a> ).
property	string	yes	The corresponding property (of the Java object specified by the enclosing <a href="#">conversion</a> )

#### 1.1.4.11. module

The `<module>` element is the root element.

Attribute	Type	Required ?	Description
id	string	yes	The id should be a dotted sequence, like a package name. In general, the module id should <i>be</i> the package name.
version	version number	yes	The version of the

			module as a dotted sequence of three numbers. Example: "1.0.0"
--	--	--	--

Contains: [<contribution>](#), [<configuration-point>](#), [<implementation>](#) , [<service-point>](#), [<schema>](#), [<sub-module>](#)

**Note:**

The version is not currently used, but a later release of HiveMind will include runtime dependency checking based on version number.

#### 1.1.4.12. parameters-schema

The `<parameters-schema>` element is identical to the [<schema>](#) element, but only appears inside [<service-point>](#), to define the schema for the parameters for a service implementation factory or service interceptor factory.

#### 1.1.4.13. rules

`<rules>` is a container for element and attribute parsing rules within an [<element>](#). These rules are responsible for converting the contributed element and its attributes into objects and object properties. The available rules are [documented separately](#) .

#### 1.1.4.14. schema

The `<schema>` element is used to describe the format of element contributions to an [<configuration-point>](#), or parameters provided to a service or interceptor factory.

Attribute	Type	Required ?	Description
id	string	yes	Assigns a local id to the schema that may be referenced elsewhere.

Contains: [<element>](#)

At a future time, the `<schema>` element will be extended to provide more options, to provide more precise control over the elements that may be provided in an `<contribution>`. At this time, a `<schema>` is simply a list of `<element>` elements.

**Note:**

When `<schema>` appears directly within [<configuration-point>](#), or `<parameters-schema>` appears directly within

[<service-point>](#), then the `id` attribute is not allowed.

#### 1.1.4.15. service-point

The `<service-point>` element defines a service extension point.

Attribute	Type	Required ?	Description
<code>id</code>	string	yes	The simple id of the service extension point. The fully qualified id for the extension point is created by prefixing with the module's id (and a dot).
<code>interface</code>	class name	yes	The fully qualified name of the Java interface supplied by this service extension point.
<code>parameters-schema-id</code>	string	no	Used to reference a <a href="#">&lt;schema&gt;</a> (in the same module, or a different one) that defines parameters used by the service. This is used when the service being defined is a <a href="#">ServiceImplementationFactory</a> or a <a href="#">ServiceInterceptorFactory</a> .
<code>parameters-occurs</code>	unbounded   0..1   1   1..n   none	no	The number of parameter element contributions allowed: <ul style="list-style-type: none"> <li>• <b>unbounded</b>: any number</li> <li>• <b>0..1</b>: optional</li> <li>• <b>1</b> (default) : required</li> <li>• <b>1..n</b>: at least one</li> <li>• <b>none</b>: none allowed</li> </ul>

Contains: [<create-instance>](#), [<interceptor>](#), [<invoke-factory>](#) , [<parameters-schema>](#)

#### 1.1.4.16. sub-module

The `<sub-module>` element is used to identify an additional HiveMind module deployment descriptor. This is used when a single JAR file contains logically distinct packages, each of which should be treated as an individual HiveMind module. This can also be useful as a way to reduce developer conflict against a single, large, central module descriptor by effectively breaking it into smaller pieces. Sub-modules identified in this way must still have their own unique module id.

Attribute	Type	Required ?	Description
descriptor	string	yes	Location of the module descriptor.

The descriptor should be specified as a relative path, either the name of another module descriptor within the same folder, or within a child folder.

### 1.1.5. Contribution Processing Rules

The concept of performing a rules-directed conversion of elements and attributes into Java objects was pioneered (to my knowledge) in the [Jakarta Digester](#) framework (which started inside Tomcat, moved to Struts, and is now available on its own).

The technique is very powerful, even in the limited subset of Digester provided by HiveMind (over time, the number of available rules will increase).

#### 1.1.5.1. Rules

Rules are attached to `<element>`s. Each rule object has two methods: the `begin()` method is invoked when the element is first encountered. The content of the element is then processed recursively (which will involve more rules). Once that completes, the `end()` method is invoked.

Note: `begin()` is invoked in the order that rules are defined within the `<rules>` element. `end()` is invoked in inverse order. This rarely makes any difference.

Element processing is based on an object stack. Several rules will manipulate the top object on the stack, setting properties based on attributes or content. The `<create-object>` rule will instantiate a new object at `begin()` and pop it off the stack at `end()`.

In several cases, rule descriptions reference the parent and child objects. The top object on the stack is the child, the object beneath that is the parent. The `<set-parent>` and `<invoke-parent>` rules are useful for creating hierarchies of objects.



### create-object

The `<create-object>` rule is used to create a new object, which is pushed onto the stack at `begin()`. The object is popped off the stack at `end()`. `<create-object>` is typically paired up with `<invoke-parent>` to connect the new object (as a child) to a parent object.

Attribute	Type	Required ?	Description
class	string	yes	The complete class name of the object to create. The class must be public, and have a no-arguments public constructor.

### custom

The `<custom>` rule is used to provide a custom implementation of the `Rule` interface. Note that any such rules must not contain any individual state, as they will be reused, possibly by multiple threads.

Attribute	Type	Required ?	Description
class	string	yes	The complete class name of the class implementing the <code>Rule</code> interface.

### invoke-parent

The `<invoke-parent>` rule is used to connect the child (top object on the stack) to its parent (the next object down). A method of the parent is invoked, passing the child as a parameter. This invocation occurs inside the rule's `begin()` method; to ensure that the child object is fully configured before being added to the parent place this rule after all properties of the child object have been configured.

Attribute	Type	Required ?	Description
method	string	yes	The name of the method to invoke on the parent object.
depth	number	no	The depth of the parent object within the object stack. The top object (the child) is at

			depth 0, and default depth of the parent is 1.
--	--	--	--

**Note:**

Top level elements should include an <invoke-parent> rule, and specify the method as addElement. This adds the created, configured object to the list of contributed objects for the [<contribution>](#) (or for service factories, adds the object as a parameter).

### push-attribute

The <push-attribute> rule reads an attribute, converts it with a translator, and pushes the result onto the stack. It will typically be combined with a [<invoke-parent>](#) to get the pushed value added to the configuration point elements (or to some parent object).

Attribute	Type	Required ?	Description
attribute	string	yes	The name of the attribute to read.

### read-attribute

The <read-attribute> rule reads an attribute from the current element, optionally translates it (from a string to some other type), and then assigns the value to a property of the top object on the object stack.

Attribute	Type	Required ?	Description
property	string	yes	The name of the property of the top object on the stack to update.
attribute	string	yes	The name of the attribute to read.
skip-if-null	boolean	no	If "true" (the default), then an omitted attribute will be ignored. If "false", the property will be updated regardless.
translator	string	no	A translator that overrides the attribute's translator.

### read-content

The <read-content> rule is similar to [<read-attribute>](#), except it concerns the content of the current element (the text wrapped by its start and end tags).

Attribute	Type	Required ?	Description
property	string	yes	The name of the property of the top object on the stack to update.

### set-module

<set-module> is used to set a property of the top object on the stack to the module which made the contribution. This is often used when some other attribute of the contribution is the name of a service or configuration extension point (but it is advantageous to defer access to the service or configuration). The module can be used to resolve names of services or configurations that are local to the contributing module.

Attribute	Type	Required ?	Description
property	string	yes	The name of the property of the top object to update with the contributing module.

### set-parent

The <set-parent> rule is used to set a property of the child object to parent object. This allows for backwards connections from child objects to parent objects.

Attribute	Type	Required ?	Description
property	string	yes	The name of the property of the child object to set.

### set-property

The <set-property> rule is used to set a property of the top object to a preset value.

Attribute	Type	Required ?	Description
property	string	yes	The name of the

			property of the child object to set.
value	string	yes	The value to set the property to. The is interpreted as with the <a href="#">smart translator</a> , meaning that conversion to normal Java types (boolean, int, etc.) will work as expected.

### 1.1.5.2. Translators

Commonly, it is necessary to perform some translation or transformation of string attribute value to convert the value into some other type, such as boolean, integer or date. This can be accomplished by specifying a translator in the [<attribute>](#) element (it also applies to element content, with the `content-translator` attribute of the [<element>](#) element).

A translator is an object implementing the [Translator](#) interface. The translator value specified in a rule may be either the complete class name of a class implementing the interface, or one of a number of builtin values.

Translators configurations consist of a translator name, and an optional initializer string. The initializer string is separated from the translator id by a comma, ex: `int,min=0` (where `min=0` is the initializer string). Initializer strings are generally in the format of `key=value[,key=value]* ...` but each Translator is free to interpret the initializer string its own way.

The following sections describe the basic translators provided with the framework. You can add additional translators by contributing to the [hivemind.Translators](#) configuration point.

#### bean

The bean translator expects its input to bean in the form `service-id:locator`. The service-id references a service implementing [BeanFactory](#).

#### Note:

This translator is contributed by the `hivemind.lib` module.

#### boolean

The boolean translator converts an input string into a boolean value. "true" is translated to true, and "false" to false.

A default value is used when the input is blank. Normally, this default is false, but the "default" key in the initializer can override this (i.e., `boolean, default=true`).

### **class**

The class translator converts a class name into a Class object. The value must be a fully qualified class name. A null input value returns null.

#### **Note:**

This translator is hard-coded, and does not appear in the [hivemind.Translators](#) configuration point.

### **configuration**

The configuration translator converts an input value into a configuration point id, then obtains the elements for that configuration point as a List. The id may be fully qualified, or a local id within the contributing module.

A blank input value returns null.

### **double**

The double translator converts the input into an double precision floating point value. It recognizes three initializer values:

- default: the default value (normally 0) to use when the input is blank
- min: a minimum acceptable value
- max: a maximum acceptable value

### **enumeration**

The enumeration translator converts input strings into enumerated values. Enumeration *requires* an initializer string, with a special format:

`enumeration, class-name, input=field-name[ , input=field-name] *`

That is, the initializer begins with the name of the class containing some number of public static fields. Input values are mapped against field names. Example:

`enumeration, java.lang.Boolean, yes=TRUE, no=FALSE`

If the input is null or empty, then the translator returns null.

### **id-list**

Translates a comma-seperated list of ids into a comma-seperated list of fully qualified ids (qualified against the contributing module). Alternately, passes the value \* through as-is. Id lists are typically used to establish ordering of items within a list, as with [<interceptor>](#).

### **instance**

The object translator converts a fully qualified class name into an object instance. The class must implement a public no-arguments constructor.

### **int**

The int translator converts the input into an integer value. It recognizes three initializer values:

- default: the default value (normally 0) to use when the input is blank
- min: a minimum acceptable value
- max: a maximum acceptable value

#### **Note:**

This translator is hard-coded, and does not appear in the [hivemind.Translators](#) configuration point.

### **long**

The long translator converts the input into an long integer (64 bit) value. It recognizes three initializer values:

- default: the default value (normally 0) to use when the input is blank
- min: a minimum acceptable value
- max: a maximum acceptable value

### **object**

The object translator is allows the caller to provide an object value in a multitude of ways. The object translator inverts the normal roles; the caller has all the power in determining how to interpret the value, and the schema takes whatever value shows up. The object translator is driven by the [hivemind.ObjectProviders](#) configuration.

### **qualified-id**

Translates an id into a fully qualified id (qualified against the contributing module's id).

## **resource**

The resource translator is used to find a resource packaged with (or near) the module's deployment descriptor. The input value is the relative path to a file. The translator converts the input value to a [Resource](#) for that file.

If the file doesn't exist, then an error is logged. If a localization of the file exists, then the Resource for that localization is returned.

## **service**

The service translator is used to lookup a service in the registry. The input value is either a local service id from the contributing module, or a fully qualified service id.

### **Note:**

This translator is hard-coded, and does not appear in the [hivemind.Translators](#) configuration point.

## **service-point**

The service translator is used to lookup a service point (not a service) in the registry. The input value is either a local service id from the contributing module, or a fully qualified service id.

## **smart**

The smart translator attempts an automatic conversion from a string value (the attribute value or element content) to a particular type. It determines the type from the property to which the value will be assigned. Smart translator makes use of the JavaBeans's PropertyEditor class for the conversion, which allows easy this translator to be used with most common primitive types, such as int, short and boolean. See the [SmartTranslator](#) documentation for more details.

In general, the smart translator is the useful for most ordinary Java type properties, unless you want to specify range constraints.

It recognizes one initializer value:

- default: the default value to use when the input is blank

### **Note:**

This translator is hard-coded, and does not appear in the [hivemind.Translators](#) configuration point.

### 1.1.6. Library Dependencies

HiveMind has a number of dependencies on other open-source frameworks. The [Ant](#) build files for HiveMind will automatically download dependencies from the [Maven](#) repository on [ibiblio](#).

File	Name	Notes
commons-logging-1.0.3.jar	<a href="#">Commons-Logging</a>	
easymock-1.1.jar	<a href="#">EasyMock testing framework</a>	Only needed by <a href="#">HiveMindTestCase</a> , which exists as the basis for your own tests.
jboss-j2ee-3.2.1.jar	<a href="#">JBoss J2EE Server</a>	Used by some services of the HiveMind library. No dependencies on JBoss itself, just on the <code>javax.ejb</code> package.
javassist-2.6.jar	<a href="#">Javassist bytecode library</a>	
oro-2.0.6.jar	<a href="#">ORO Regular Expressions</a>	
spring-full-1.0.1.jar	<a href="#">Spring</a>	Used by the <a href="#">hivemind.lib.SpringLookupFactory</a> service.

Typically, all you need is the HiveMind libraries, Javassist, ORO and commons-logging. Your EJB container will provide the `javax.ejb` classes. Obviously, you should include Spring if you are using Spring, and EasyMock if you are writing tests using the `HiveMindTestCase` base class.

In most cases, HiveMind has been built against a "handy" version; in all likelihood you can vary the exact version of a dependency to suite your existing environment. Just remember to write some tests!

#### Note:

HiveMind is explicitly designed to be used with JDK 1.3 and above. It uses no features from JDK 1.4 that aren't also available on JDK 1.3.

## 1.2. History of Changes

[RSS](#)



### **1.2.1. Version 1.0-rc-1 (Aug 25 2004)**

- Remove support for Simple Data Language ... it's all XML again. (HLS)
- Re-work part of PipelineFactory to take advantage of object references. (HLS)
- Make the service-id of <invoke-factory> optional and default to hivemind.BuilderFactory. (HLS)
- Change the hivemind.Startup configuration to take an object reference, not a service id. (HLS)
- SmartTranslator should differentiate between blank strings and null input (HLS) Thanks to Michael Frericks. Fixes [HIVEMIND-29](#).
- Improvements to HiveBuild to properly handle changing versions or useages of artifacts. (HLS)
- Add ability to mark attributes of an element as unique, such that duplicate values in contributions result in errors. (HLS) Thanks to Johan Lindquist. Fixes [HIVEMIND-43](#).
- Add checks to SchemaProcessorImpl for empty stack conditions (HLS) Fixes [HIVEMIND-41](#).
- Add parameters-occurs attribute to <service-point> element. (HLS) Fixes [HIVEMIND-33](#).
- Specify location in all module deployment descriptor parse exceptions. (HLS) Fixes [HIVEMIND-23](#).
- Add Quick Reference Sheet. (HLS) Thanks to Stefan Liebig. Fixes [HIVEMIND-42](#).
- Add getCause ( ) method to ApplicationRuntimeException (HLS) Thanks to Luke Blanshard. Fixes [HIVEMIND-16](#).
- Add polling methods to Registry. (HLS) Thanks to Naresh Sikha. Fixes [HIVEMIND-37](#).
- Add polling methods to BeanFactory. (HLS) Thanks to Naresh Sikha. Fixes [HIVEMIND-36](#).
- Fix broken synchronization in ThreadedServiceModel and PooledServiceModel that could make them randomly fail when creating a service by invoking a factory. (HLS) Thanks to James Carman. Fixes [HIVEMIND-44](#).
- Check for <sub-module> references that do not exist. (HLS) Thanks to Johan Lindquist. Fixes [HIVEMIND-34](#).

### **1.2.2. Version 1.0-beta-2 (Aug 1 2004)**

- Removed dependency on Werkz. (KW) Fixes [HIVEMIND-6](#).
- Added link to the Jakarta mailing lists page. (HLS)
- Modified the build scripts to properly include variable info when compiling. (HLS) Thanks to Achim Hügen. Fixes [HIVEMIND-21](#).
- Moved the Ant build scripts to a new directory, hivebuild, in preparation for making hivebuild reusable on new projects. (HLS)
- Added protected method constructRegistry() to HiveMindFilter. (HLS)

- Renamed existing 'object' translator to 'instance', and created a new 'object' translator with great flexibility. Extend BuilderFactory to add a set-object element that leverages the object translator. (HLS)
- Created service-property object translator. (HLS)
- Added a version of `Registry.getService()` that omits the service id (but requires that exactly one service point implements the service interface). (HLS) Thanks to Marcus Brito. Fixes [HIVEMIND-20](#).
- Extended the BuilderFactory to autowire services. (HLS) Fixes [HIVEMIND-22](#).
- Added a new module that contains HiveMind example code. (HLS)
- Fixed some latent bugs related to submodules inside the constructRegistry task. Made some more improvements to the hivebuild scripts. (HLS)
- Updated the download location for the Forrest distribution. (HLS)
- Added more examples and examples documentation. (HLS)
- Added StrictErrorHandler, an implementation of ErrorHandler that always throws an ApplicationRuntimeException. (HLS)
- Moved the code for the Grabber Ant task into the tree and improve the build scripts to dynamically compile and use it. (HLS)
- Typo in jar-module.xml causes broken build if junit library is missing (HLS) Thanks to Johan Lindquist. Fixes [HIVEMIND-31](#).
- Made a number of changes to ensure HiveMind compatibility with JDK 1.3. (HLS) Fixes [HIVEMIND-35](#).
- Changed some unit tests to adapt to platform line endings. (HLS) Fixes [HIVEMIND-26](#).
- Fix the HiveDoc XSL to use XML (not SDL) output. (HLS) Thanks to Johan Lindquist. Fixes [HIVEMIND-46](#).

### **1.2.3. Version 1.0-beta-1 (Jun 26 2004)**

- Added change log. (HLS)
- Refactored ClassFab and related classes for easier reuse outside of HiveMind. Added a new suite of tests related to ClassFab.(HLS)
- Created two new services in hivemind-lib for creating default implementations of arbitrary interfaces ([DefaultImplementationBuilder](#)) and for using that to create placeholder services ([PlaceholderFactory](#)).(HLS)
- Created MessageFormatter class as a wrapper around ResourceBundle and an easy way for individual packages to gain access to runtime messages. (HLS)
- Modified the read-attribute rule to allow a translator to be specified (overriding the translator for the attribute).(HLS)
- Added the qualified-id and id-list translators.(HLS)
- Added the [hivemind.lib.PipelineFactory](#) and related code, schemas, tests and documentation. (HLS)
- Enhance logging of exceptions when setting a service property to a contribution (HLS)

Fixes [HIVEMIND-4](#).

- Added service [hivemind.lib.BeanFactoryBuilder](#). (HLS)
- Removed the <description> element from the module descriptor format; descriptions are now provided as enclosed text for element that support descriptions. (HLS)
- Changed the MethodMatcher classes to use a MethodSignature rather than a Method. (HLS)
- Changed MessageFormatter to automatically convert Throwables into their message or class name. (HLS)
- Added FileResource. (HLS)
- Extended [hivemind.BuilderFactory](#) to be able to set the ClassResolver; for a service implementation, and to autowire common properties (log, messages, serviceId, errorHandler, classResolver) if the properties are writeable and of the correct type. (HLS)
- Added methods newControl(), newMock(), addControl(), replayControls() and verifyControls() to HiveMindTestCase to simplify test cases that use multiple [EasyMock](#) mock objects. (HLS)
- Changed HiveMindFilter to log a message after it stores the registry into the servlet context. (HLS)
- Restore the getConfiguration() and expandSymbols() methods to the Registry interface. (HLS) Fixes [HIVEMIND-11](#).
- SimpleDataLanguageParser calls the ContentHandler with a null namespace argument instead of "". That leads to some problems if you want to use transformers. (HLS) Thanks to Dieter Bogdoll. Fixes [HIVEMIND-9](#).
- Fix how certain translator messages are generated to avoid unit test failures. (HLS) Thanks to Achim Hügen. Fixes [HIVEMIND-7](#).
- Modify the build files to enable debugging by default. (HLS) Fixes [HIVEMIND-12](#).
- Added validation of id attributes in module deployment descriptors (using ORO regular expressions). (HLS)
- Fix some typos in definition of the [hivemind.lib.NameLookup](#) service. (HLS)
- Fix a mistake in the BuilderFactory's set-object element, and add integration tests. (HLS) Thanks to Naresh Sikha. Fixes [HIVEMIND-25](#).

## 1.3. Todo List

### 1.3.1. Release 1.0

- [lib] JMX Integration # HLS

## 1.4. HiveMind Downloads

HiveMind distributions are available from the Apache Mirrors. HiveMind is packaged somewhat differently than most other Apache projects, in that the main distribution includes

binary *and* source, but that documentation is seperate:

- `hivemind-release.tar.gz` -- Combined binary/source distribution
- `hivemind-release.zip` -- Combined binary/source distribution (about twice the size of the `.tar.gz`)
- `hivemind-release-docs.tar.gz` -- The HiveMind documentation (the same as this site)

Each file also has a MD5 checksum file, so you can verify that what you download is valid, and a GPG key (`.asc`) to further verify that there has been no tampering.

**Note:**

Under Internet Explorer, the `.tar.gz` files do not download with the correct file name. Download them, rename them to `.tar.gz` and then open them using WinZip.

## 1.5. CVS Access

Anonymous CVS access is available as:

```
:pserver:anoncvs@cvs.apache.org:/home/cvspublic/jakarta-hivemind
```

In addition, the [CVS repository may be browsed online](#).

## 1.6. Tutorials and Information

### 1.6.1. Bootstrapping the Registry

Before you can access the configuration points and services defined in your application's module deployment descriptors, you need a registry; here we'll describe how to construct the registry.

The key class here is [RegistryBuilder](#), which contains code for locating and parsing the module deployment descriptors and constructing a registry from the combined data. The descriptors are all found on the class path; they'll include the descriptors for HiveMind itself with descriptors packaged into your application's JARs.

**Note:**

As HiveMind grows in popularity, we may start to see third party frameworks come bundled with HiveMind module deployment descriptors ... but it's too soon for that, now.

Let's examine how all this comes together. The layout of the project is shown below.

[Project Layout]

### **1.6.1.1. Service Interfaces and Implementations**

The first step is to define the service interface:

```
package hivemind.examples;

public interface Adder
{
    public int add(int arg0, int arg1);
}
```

Next we need an implementation for that service:

```
package hivemind.examples.impl;

import hivemind.examples.Adder;

public class AdderImpl implements Adder
{
    public int add(int arg0, int arg1)
    {
        return arg0 + arg1;
    }
}
```

The example includes three additional interfaces and matching implementations: for a Subtractor, Multiplier, Divider, and lastly, a Calculator that combines them together:

```
package hivemind.examples;

public interface Calculator extends Adder, Subtractor, Multiplier, Divider
{
}
```

The Calculator implementation will require some wiring; it expects that each of the other four services (Adder, Subtractor, Multiplier and Divider) will be plugged into it:

```
package hivemind.examples.impl;

import hivemind.examples.Adder;
import hivemind.examples.Calculator;
import hivemind.examples.Divider;
import hivemind.examples.Multiplier;
import hivemind.examples.Subtractor;

public class CalculatorImpl implements Calculator
{
}
```

```

private Adder _adder;
private Subtractor _subtractor;
private Multiplier _multiplier;
private Divider _divider;

public void setAdder(Adder adder)
{
    _adder = adder;
}

public void setDivider(Divider divider)
{
    _divider = divider;
}

public void setMultiplier(Multiplier multiplier)
{
    _multiplier = multiplier;
}

public void setSubtractor(Subtractor subtracter)
{
    _subtractor = subtracter;
}

public int add(int arg0, int arg1)
{
    return _adder.add(arg0, arg1);
}

public int subtract(int arg0, int arg1)
{
    return _subtractor.subtract(arg0, arg1);
}

public int multiply(int arg0, int arg1)
{
    return _multiplier.multiply(arg0, arg1);
}

public int divide(int arg0, int arg1)
{
    return _divider.divide(arg0, arg1);
}
}

```

### 1.6.1.2. Module Deployment Descriptor

Finally, we need the HiveMind module deployment descriptor, `hivemodule.xml`.

The module descriptor creates each of the services in terms of an interface, and an implementation. In addition, each service gets its own logging interceptor.

```
<?xml version="1.0"?>
<module id="hivemind.examples" version="1.0.0">
  <service-point id="Adder" interface="hivemind.examples.Adder">
    <create-instance class="hivemind.examples.impl.AdderImpl"/>
    <interceptor service-id="hivemind.LoggingInterceptor"/>
  </service-point>

  <service-point id="Subtractor" interface="hivemind.examples.impl.SubtractorImpl">
    <create-instance class="hivemind.examples.impl.AdderImpl"/>
    <interceptor service-id="hivemind.LoggingInterceptor"/>
  </service-point>

  <service-point id="Multiplier" interface="hivemind.examples.Multiplier">
    <create-instance class="hivemind.examples.impl.MultiplierImpl"/>
    <interceptor service-id="hivemind.LoggingInterceptor"/>
  </service-point>

  <service-point id="Calculator" interface="hivemind.examples.Calculator">
    <invoke-factory>
      <!-- Autowires service properties based on interface! -->
      <constuct class="hivemind.examples.impl.CalculatorImpl"/>
    </invoke-factory>
    <interceptor service-id="hivemind.LoggingInterceptor"/>
  </service-point>
</module>
```

Here we've chosen to have the module id, `hivemind.examples`, match the package name but that is not an absolute requirement.

The interesting part is the use of the [hivemind.BuilderFactory](#) to construct the Calculator service and connect it to the other four services.

### 1.6.1.3. Building the Registry

Before your code can access any services (or configuration points), it must construct the [Registry](#). The Registry is the applications gateway into the services and configurations managed by HiveMind.

```
package hivemind.examples;

import org.apache.hivemind.Registry;
import org.apache.hivemind.impl.RegistryBuilder;

public class Main
{
    public static void main(String[] args)
    {
        int arg0 = Integer.parseInt(args[0]);
    }
}
```

```

    int arg1 = Integer.parseInt(args[1]);

    Registry registry = RegistryBuilder.constructDefaultRegistry();

    Calculator c =
        (Calculator) registry.getService(Calculator.class);

    System.out.println("Inputs " + arg0 + " and " + arg1);

    System.out.println("Add    : " + c.add(arg0, arg1));
    System.out.println("Subtract: " + c.subtract(arg0, arg1));
    System.out.println("Multiply: " + c.multiply(arg0, arg1));
    System.out.println("Divide  : " + c.divide(arg0, arg1));
}
}

```

[RegistryBuilder](#) contains a static method for constructing a Registry, which is suitable for most situations.

Now that we have the registry, we can use the Calculator interface as a key for finding the Calculator implementation. In real applications, where there will often be multiple services implementing the same interface, we would have to specify a fully qualified service id as well.

Using the reference to the Calculator service, we can finally invoke the `add()`, `subtract()`, `multiply()` and `divide()` methods.

#### **1.6.1.4. Building the Example**

Building and running the example using [Ant](#) is a snap; all the details are in the `build.xml`:

```

<?xml version="1.0"?>

<project name="HiveMind Adder Example" default="jar">

    <property name="java.src.dir" value="src/java"/>
    <property name="test.src.dir" value="src/test"/>
    <property name="conf.dir" value="src/conf"/>
    <property name="descriptor.dir" value="src/descriptor"/>
    <property name="target.dir" value="target"/>
    <property name="classes.dir" value="${target.dir}/classes"/>
    <property name="test.classes.dir" value="${target.dir}/test-classes"/>
    <property name="example.jar" value="${target.dir}/hivemind-examples.jar"/>
    <property name="lib.dir" value="lib"/>
    <property name="junit.temp.dir" value="${target.dir}/junit-temp"/>
    <property name="junit.reports.dir" value="${target.dir}/junit-reports"/>

    <path id="build.class.path">
        <fileset dir="${lib.dir}">
            <include name="*.jar"/>

```



```
</fileset>
</path>

<path id="test.build.class.path">
  <path refid="build.class.path"/>
  <path location="${classes.dir}"/>
</path>

<path id="run.class.path">
  <path refid="build.class.path"/>
  <pathelement location="${classes.dir}"/>
  <pathelement location="${descriptor.dir}"/>
  <pathelement location="${conf.dir}"/>
</path>

<path id="test.run.class.path">
  <path refid="run.class.path"/>
  <path location="${test.classes.dir}"/>
</path>

<target name="clean" description="Delete all derived files.">
  <delete dir="${target.dir}" quiet="true"/>
</target>

<target name="compile" description="Compile all Java code.">
  <mkdir dir="${classes.dir}"/>
  <javac srcdir="${java.src.dir}" destdir="${classes.dir}" classpathref="build.class.path"/>
</target>

<target name="compile-tests" description="Compile test classes." depends="compile">
  <mkdir dir="${test.classes.dir}"/>
  <javac srcdir="${test.src.dir}" destdir="${test.classes.dir}" classpathref="test.build.class.path"/>
</target>

<target name="run-tests" description="Run unit tests." depends="compile-tests">
  <mkdir dir="${junit.temp.dir}"/>
  <mkdir dir="${junit.reports.dir}"/>

  <junit haltonfailure="off" failureproperty="junit-failure" tempdir="${junit.temp.dir}">
    <classpath refid="test.run.class.path"/>

    <formatter type="xml"/>
    <formatter type="plain"/>
    <formatter type="brief" usefile="false"/>

    <batchtest todir="${junit.reports.dir}">
      <fileset dir="${test.classes.dir}">
        <include name="**/Test*.class"/>
      </fileset>
    </batchtest>
  </junit>

  <fail if="junit-failure" message="Some tests failed."/>
</target>
```

```
</target>

<target name="jar" description="Construct the JAR file." depends="compile,run-tests">
  <jar destfile="${example.jar}">
    <fileset dir="${classes.dir}" />
    <fileset dir="${descriptor.dir}" />
  </jar>
</target>

<target name="run" depends="compile" description="Run the Adder service.">
  <java classname="hivemind.examples.Main" classpathref="run.class.path" fork="true">
    <arg value="11" />
    <arg value="23" />
  </java>
</target>

</project>
```

The important part is to package both the classes and the HiveMind module deployment descriptor into the JAR.

The only other oddity was to add `src/conf` to the runtime classpath; this is to include the `log4j.properties` configuration file; otherwise Log4J will write console errors about missing configuration.

#### 1.6.1.5. Running the Examples

```
bash-2.05b$ ant run
Buildfile: build.xml

compile:
  [mkdir] Created dir: C:\workspace\hivemind-example\target\classes
  [javac] Compiling 15 source files to C:\workspace\hivemind-example\target\classes

run:
  [java] Inputs 11 and 23
  [java] Add      : 34
  [java] Subtract: -12
  [java] Multiply: 253
  [java] Divide   : 0

BUILD SUCCESSFUL
Total time: 3 seconds
```

#### 1.6.2. Inversion of Control

Seems like **Inversion of Control** is all the rage these days. The Avalon project is completely based around it. Avalon uses detailed assembly descriptions to tie services together ... there's

no way an Avalon component can "look up" another component; in Avalon you explicitly connect services together.

That's the basic concept of Inversion of Control; you don't create your objects, you describe how they should be created. You don't directly connect your components and services together in code, you describe which services are needed by which components, and the container is responsible for hooking it all together. The container creates all the objects, wires them together by setting the necessary properties, and determines when methods are invoked.

More recently, this concept has been renamed Dependency Injection.

There are three different implementation pattern types for IoC:

type-1	Services need to implement a dedicated interface through which they are provided with an object from which they can look up dependencies (other services). This is the pattern used by the earlier containers provided by Avalon.
type-2	Services dependencies upon are assigned via JavaBeans properties (setter methods). Both HiveMind and <a href="#">Spring</a> use this approach.
type-3	Services dependencies are provided as constructor parameters (and are not exposed as JavaBeans properties). This is the exclusive approach used by PicoContainer, and is also used in HiveMind and Spring.

HiveMind is a much looser system than Avalon. HiveMind doesn't have an explicit assembly stage; it wires together all the modules it can find at runtime. HiveMind is responsible for creating services (including core implementations and interceptors). It is quite possible to create service factories that do very container-like things, including connecting services together. [hivemind.BuilderFactory](#) does just that, instantiating an object to act as the core service implementation, then setting properties of the object, some of which are references to services and configuration point element data.

In HiveMind, you are free to mix and match type-2 (property injection) and type-3 (constructor injection), setting some (or all) dependencies via a constructor and some (or all) via JavaBeans properties.

In addition, JavaBeans properties (for dependencies) can be write-only. You only need to provide a setter method. The properties are properties of the core service implementation, there is no need for the accessor methods to be part of the service interface.

HiveMind's lifecycle support is much more rudimentary than Avalon's. Your service implementations can get `hivemindcallbacks` when they are first created, and when they are discarded, by implementing certain interfaces.

Purist inversion of control, as in Avalon, may be more appropriate in well-constrained systems containing untrusted code. HiveMind is a layer below that, not an application server, but a microkernel. Although I can see using HiveMind as the infrastructure of an application server, even an Avalon application server, it doesn't directly overlap otherwise.

### 1.6.3. HiveMind Localization

Every HiveMind module may have its own set of messages. Messages are stored alongside the module deployment descriptor, as `META-INF/hivemodule.properties` (within the module's JAR).

**Note:**

In actuality, the name of the properties file is created by stripping off the extension (".xml") from the descriptor name and appending the localization code and ".properties". This is relevant only if you load your module deployment descriptors from a non-standard location, possibly via the `<sub-module>` element.

Services can gain access to localized messages, as an instance of [Messages](#), which includes methods for accessing messages and formatting messages with arguments.

In a module descriptor, within the `<contribution>` and `<invoke-factory>` elements, you can reference a localized message in an attribute or element content simply by prefixing the message key with '%'. Examples:

```
<contribution configuration-id=...>
  <some-item <message="%message.key">
    %other.message.key
  </some-item>
</contribution>
```

The two keys (`message.key` and `other.message.key`) are searched for in the *contributing* module's messages.

HiveMind gracefully recovers from undefined messages. If a message is not in the properties file, then HiveMind provides a substitute value by converting the key to upper-case and adding brackets, i.e. `[MESSAGE.KEY]`. This allows your application to continue running, but clearly identifies missing messages.

By adding additional files, message localization can be accomplished. For example, adding a second file, `META-INF/hivemodule_fr.properties` would provide French language localizations. Any common keys between the two files defer to the more specific

file.

#### **1.6.3.1. Setting the locale**

When a [Registry](#) is created by the [RegistryBuilder](#), a locale is specified. This is the locale for the Registry and, by extension, for all Modules in the registry. The locale may not be changed.

#### **1.6.4. HiveMind Multi-Threading**

HiveMind is specifically targetted for J2EE: deployment in a WAR or EAR, particularly as part of a [Tapestry](#) application. Of course, J2EE is not a requirement, and HiveMind is quite useful even in a simple, standalone environment.

In the world of J2EE, multi-threading is always an issue. HiveMind services are usually singletons, and must be prepared to operate in a multi-threaded environment. That means services should not have any specific state, much like a servlet.

##### **1.6.4.1. Construction State**

HiveMind expects that initially, work will progress in a single startup thread. This is the early state, the construction state, where the module deployment descriptors are located and parsed, and the contents used to assemble the registry; this is the domain of [RegistryBuilder](#).

The construction activities are not thread-safe. This includes the parser, and other code (virtually all of which is hidden from your application).

The construction state ends when the `RegistryBuilder` returns the [Registry](#) from method `constructRegistry()`. The registry is thread-safe.

##### **1.6.4.2. Runtime State**

Everything that occurs with the Registry and modules must be thread-safe. Key methods are always synchronized. In particular, the methods that construct a service and construct configuration point elements are thread-safe. Operations such as building the interceptor stack, instantiating core service implementations, and converting XML to Java objects operate in a thread-safe manner. However, different threads may be building different services simultaneously. This means that, for example, an interceptor service implementation must still be thread-safe, since it may be called upon to generate interceptors for two or more different services simultaneously.

On the other hand, the Java objects constructed from XML [rules](#) don't need to be thread-safe, since that construction is synchronized properly ... only a single thread will be

converting XML to Java objects for any single configuration point.

#### 1.6.4.3. Managing Service State

When services simply must maintain state *between* method invocations, there are several good options:

- Store the data in an object passed to or returned from the service
- Make use of the [hivemind.ThreadLocalStorage](#) service to store the data in a thread-local map.
- Make use of the [threaded](#) or [pooled](#) service models, which allow a service to keep its state between service method invocations.

#### 1.6.5. HiveMind Servlet Filter

HiveMind includes a feature to streamline the use of HiveMind within a web application: a servlet filter that can automatically construct the HiveMind Registry and ensure that end-of-request thread cleanup occurs.

The filter class is [HiveMindFilter](#). It constructs a standard HiveMind Registry when initialized, and will shutdown the Registry when the containing application is undeployed.

Each request will be terminated with a call to the [Registry's cleanupThread\(\) method](#), which will cleanup any thread-local values, including service implementations that are bound to the current thread.

The HiveMindFilter class includes a static method for accessing the Registry.

##### 1.6.5.1. Deployment Descriptor

To make use of the filter, it must be declared inside the web deployment descriptor (web.xml). Filters can be attached to servlets, or URL patterns, or both. Here's an example:

```
<filter>
  <filter-name>HiveMindFilter</filter-name>
  <filter-class>org.apache.hivemind.servlet.HiveMindFilter</filter-class>
</filter>

<servlet>
  <servlet-name>MyServlet</servlet-name>
  <servlet-class>myco.servlets.MyServlet</servlet-class>
</servlet>

<filter-mapping>
  <filter-name>HiveMindFilter</filter-name>
  <servlet-name>MyServlet</servlet-name>
</filter-mapping>
```

### 1.6.6. Overriding a Service

It is not uncommon to want to override an existing service and replace it with a new implementation. This goes beyond simply intercepting the service ... the goal is to replace the original implementation with a new implementation. This occurs frequently in [Tapestry](#) where frequently an existing service is replaced with a new implementation that handles application-specific cases (and delegates most cases to the default implementation).

**Note:**

Plans are afoot to refactor [Tapestry](#) 3.1 to make considerable use of HiveMind. Many of the ideas represented in HiveMind germinated in earlier Tapestry releases.

HiveMind doesn't have an explicit mechanism for accomplishing this ... that's because it's reasonable to replace and wrap existing services just with the mechanisms already available.

#### 1.6.6.1. Step One: A non-overridable service

To describe this technique, we'll start with a ordinary, every day service. In fact, for discussion purposes, there will be two services: Consumer and Provider. Ultimately, we'll show how to override Provider. Also for discussion purposes, we'll do all of this in a single module, though (of course) you can as easily split it up across many modules.

To begin, we'll define the two services, and set Provider as a property of Consumer:

```
<module id="ex.override" version="1.0.0">
  <service-point id="Provider" interface="ex.override.Provider">
    <create-instance class="ex.override.impl.ProviderImpl"/>
  </service-point>

  <service-point id="Consumer" interface="ex.override.Consumer">
    <invoke-factory>
      <construct class="ex.override.impl.Consumer">
        <set-service property="provider" service-id="Provider"/>
      </construct>
    </invoke-factory>
  </service-point>
</module>
```

#### 1.6.6.2. Step Two: Add some indirection

In this step, we still have just the two services ... Consumer and Provider, but they are linked together less explicitly, by using substitution symbols.

```
<module id="ex.override" version="1.0.0">
  <service-point id="Provider" interface="ex.override.Provider">
```

```
<create-instance class="ex.override.impl.ProviderImpl"/>
</service-point>

<contribution configuration-id="hivemind.FactoryDefaults">
  <default symbol="ex.override.Provider" value="ex.override.Provider"/>
</contribution>

<service-point id="Consumer" interface="ex.override.Consumer">
  <invoke-factory>
    <construct class="ex.override.impl.Consumer">
      <set-service property="provider" service-id="{ex.override.Provider}"/>
    </construct>
  </invoke-factory>
</service-point>
</module>
```

The indirection is in the form of the symbol `ex.override.Provider`, which evaluates to the service id `ex.override.Provider` and the end result is the same as step one. We needed to use a fully qualified service id because, ultimately, we don't know in which modules the symbol will be referenced.

### 1.6.6.3. Step Three: Override!

The final step is to define a second service and slip it into place. For kicks, the `OverrideProvider` service will get a reference to the original `Provider` service.

```
<module id="ex.override" version="1.0.0">
  <service-point id="Provider" interface="ex.override.Provider">
    <create-instance class="ex.override.impl.ProviderImpl"/>
  </service-point>

  <contribution configuration-id="hivemind.FactoryDefaults">
    <default symbol="ex.override.Provider" value="ex.override.Provider"/>
  </contribution>

  <service-point id="OverrideProvider" interface="ex.override.Provider">
    <invoke-factory>
      <construct class="ex.override.impl.OverrideProviderImpl">
        <set-service property="defaultProvider" service-id="Provider"/>
      </construct>
    </invoke-factory>
  </service-point>

  <!-- ApplicationDefaults overrides FactoryDefaults -->

  <contribution id="hivemind.ApplicationDefaults">
    <default symbol="ex.override.Provider" value="ex.override.OverrideProvider"/>
  </contribution>

  <!-- Consumer unchanged from step 2 -->

  <service-point id="Consumer" interface="ex.override.Consumer">
```



```
<invoke-factory>
  <construct class="ex.override.impl.Consumer">
    <set-service property="provider" service-id="{ex.override.Provider}" />
  </invoke-factory>
</service-point>
</module>
```

The new service, `OverrideProvider`, gets a reference to the original service using its real id. It can't use the symbol that the `Consumer` service uses, because that would end up pointing it at itself. Again, in this example it's all happening in a single module, but it could absolutely be split up, with `OverrideProvider` and the configuration to [hivemind.ApplicationDefaults](#) in an entirely different module.

[hivemind.ApplicationDefaults](#) overrides [hivemind.FactoryDefaults](#). This means that the `Consumer` will be connected to `ex.override.OverrideProvider`.

Note that the `<service-point>` for the `Consumer` doesn't change between steps two and three.

#### 1.6.6.4. Limitations

The main limitation to this approach is that you can only do it once for a service; there's no way to add an `EvenMoreOverridenProvider` service that wraps around `OverrideProvider` (that wraps around `Provider`). Making multiple contributions to the [hivemind.ApplicationDefaults](#) configuration point with the name symbol name will result in a runtime error ... and unpredictable results.

This could be addressed by adding another source to the [hivemind.SymbolSources](#) configuration.

To be honest, if this kind of indirection becomes extremely frequent, then HiveMind should change to accomodate the pattern, perhaps adding an `<override>` element, similar to a `<interceptor>` element.

#### 1.6.7.

### 1.7. Reports

#### 1.7.1. Project License

Apache License  
Version 2.0, January 2004

<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.
3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.
4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:
  - (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
  - (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
  - (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
  - (d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one

of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.
6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.
7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.
8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[ ]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");  
you may not use this file except in compliance with the License.  
You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

### **1.7.2.**

## **2. Module: hivemind**

### **2.1. Services**

#### **2.1.1. hivemind.BuilderFactory Service**

The [BuilderFactory](#) service is a service implementation factory ... a service that is used to construct other services.

The builder factory takes a single parameter element (usually with nested elements):

```
<construct
  class="..." autowire-services="..." log-property="..." messages-property="..."
  service-id-property="..." initialize-method="..."
  error-handler-property="..." class-resolver-property="...">

  <log/>
  <messages/>
  <service-id/>
  <error-handler/>
  <class-resolver/>
  <string> ... </string>
  <boolean> ... </boolean>
  <configuration> ... </configuration>
  <int> ... </int>
  <long> ... </long>
  <resource> ... </resource>
  <service> ... </service>
  <object> ... </object>

  <event-listener service-id="..." event-type-name="..." />
  <set property="..." value="..." />
  <set-configuration property="..." configuration-id="..." />
  <set-resource property="..." path="..." />
  <set-service property="..." service-id="..." />
  <set-object property="..." value="..." />
</construct>
```

The attributes of the `construct` element are used to specify the implementation class and set common service properties. Nested elements supply the constructor parameters and configure other specific properties of the implementation (the `set-...` elements).

**Note:**

BuilderFactory is a complex tool, with support for both constructor dependency injection and property dependency injection. Many of the options are rarely used; the most general purpose and most frequently used are [set](#), [set-object](#) and [event-listener](#) (along with [autowiring of certain properties](#)).

### 2.1.1.1. construct

Attribute	Required ?	Description
autowire-services	no	If true (the default), then the BuilderFactory will attempt to automatically wire any services that are not otherwise set. Any property that is writable, and whose type is an interface, will be autowired. For such properties, it is required that

		there be a single service point that implements the interface. An error will be logged if no service point implements the interface, or if multiple service points implement the interface.
class	yes	The fully qualified name of the class to instantiate.
class-resolver-property	no	The property to receive the module's <a href="#">ClassResolver</a> .
error-handler-property	no	The name of a property to receive the module's <a href="#">ErrorHandler</a> instance (which is used to report recoverable errors).
initialize-method	no	The name of a method (public, no parameters) to invoke after the service is constructed, to allow it to perform any final initialization before being put into use.
log-property	no	The name of a property which will be assigned a <code>org.apache.commons.logging.Log</code> instance for the service. The Log is created from the complete service id (not the name of the class). If omitted, no Log will be assigned.
messages-property	no	Allows the <a href="#">Messages</a> for the module to be assigned to a property of the instance.
service-id-property	no	Allows the service id of the <i>constructed</i> service to be assigned to a property of the service implementation.

The remaining elements are enclosed by the <construct> element, and are used to supply constructor parameters and configure properties of the constructed service implementation.

#### 2.1.1.2. Autowiring

BuilderFactory will automatically set certain common properties of the service implementation. By using standard names (and standard types), the need to specify attributes `log-property`, `error-handler-property`, etc. is avoided. Simply by having a writable property with the correct name and type is sufficient:

Property name	Property Type
<code>classResolver</code>	<a href="#">ClassResolver</a>
<code>errorHandler</code>	<a href="#">ErrorHandler</a>
<code>log</code>	<code>org.apache.commons.logging.Log</code>
<code>messages</code>	<a href="#">Messages</a>
<code>serviceId</code>	<code>String</code>

In addition, if the `initialize-method` attribute is *not* specified, and the service implementation includes a public method `initializeService()` (no parameters, returns void), then `initializeService()` will be invoked as the initializer.

### 2.1.1.3. Constructor Parameter Elements

The following table summarizes the elements which can be used to specify constructor parameters for the class to instantiate. These elements can be mixed freely with the properties configuring elements. It is important to know that the number, type, and order of the constructor parameter elements determine the constructor that will be used to instantiate the implementation.

Element	Matched Parameter Type	Passed Parameter Value
<code>error-handler</code>	<a href="#">ErrorHandler</a>	The module's ErrorHandler, user to report recoverable errors.
<code>log</code>	<code>org.apache.commons.logging.Log</code>	The Log is created from the complete service id (not the name of the class) of the created service.
<code>messages</code>	<code>org.apache.hivemind.Messages</code>	The <a href="#">Messages</a> object of the invoking module.
<code>object</code>	<i>variable</i>	As determined by the object translator, this is decidedly free-form. See <a href="#">hivemind.ObjectProviders</a> .



service-id	java.lang.String	The service id of the <i>constructed</i> service.
string	java.lang.String	This element's content.
boolean	boolean	This element's content. Must be either "true" or "false".
configuration	java.util.List	The List of the elements of the configuration specified by this element's content as a configuration id. The id can either be a simple id for a configuration within the same module as the constructed service, or a complete id.
int	int	This element's content parsed as an integer value.
long	long	This element's content parsed as a long value.
resource	org.apache.hivemind.Resource	This element's content parsed as a path to a <a href="#">Resource</a> , which is relative to the contributing module's deployment descriptor. If available, a localized version of the Resource will be selected.
service	interface corresponding to specified service	The implementation of the service with the id given in this element's content. The id can either be a simple id for a service within the same module as the constructed service, or a complete id.

#### 2.1.1.4. Service Property Configuring Elements

##### event-listener

Attribute	Description
service-id	The service which produces events. The service must provide, in its service interface, the necessary add and remove listener methods.

name	The name of an event set to be registered. If not specified, all applicable event sets are used.
------	--

If the name attribute is not specified, then BuilderFactory will register for all applicable event sets. For each event set provided by the specified service, BuilderFactory will check to see if the service instance being constructed implements the corresponding listener interface ... if so, the constructed service instance is added as a listener. When the name attribute is specified, the constructed service instance is registered as a listener of just that single type.

Event notifications go directly to the constructed service instance; they don't go through any proxies or interceptors for the service. The service *instance* must implement the listener interface, the constructed service's service interface *does not* have to extend the listener interface. In other words, event notifications are "behind the scenes", not part of the public API of the service.

It is perfectly acceptable to include multiple <event-listener> elements for a number of different event producing services.

It is not enough for the event producer service to have an add listener method (i.e., `addPropertyChangeListener(PropertyChangeListener)`). To be recognized as an event set, there must also be a corresponding remove listener method (i.e., `removePropertyChangeListener(PropertyChangeListener)`), even though BuilderFactory does not make use of the remove method. This is an offshoot of how the JavaBeans API defines event sets.

## set

Attribute	Description
property	The name of the property to set.
value	A value to assigned to the property. The value will be converted to an appropriate type for the property.

## set-configuration

Attribute	Description
property	The name of the property to set.
configuration-id	The id of a configuration, either a simple id for a configuration within the same module as the constructed service, or a complete id. The property will be assigned a <code>List</code> of the elements of the configuration.

### set-object

Attribute	Description
property	The name of the property to set.
value	The <i>selector</i> used to find an object value. The selector consists of a prefix (such as "service" or "configuration"), a colon, and a <i>locator</i> whose interpretation is defined by the prefix. For example, <code>service:MyService</code> . See <a href="#">hivemind.ObjectProviders</a> .

### set-resource

Attribute	Description
property	The name of the property to set.
path	The path to a <a href="#">Resource</a> , relative to the contributing module's deployment descriptor. If available, a localized version of the Resource will be selected.

### set-service

Attribute	Description
property	The name of the property to set.
service-id	The id of a service, either a simple id for a service within the same module as the constructed service, or a complete id. The property will be assigned the service.

#### 2.1.2. hivemind.LoggingInterceptor Service

The [LoggingInterceptor](#) service is used to add logging capability to a service, i.e.:

```
<interceptor service-id="hivemind.LoggingInterceptor">
  <include method="..." />
  <exclude method="..." />
</interceptor>
```

The service make take parameters (which control which methods will be logged).

The logging interceptor uses a Log derived from the service id (of the service to which

logging is being added).

The service logs, at debug level, the following events:

- Method entry (with parameters)
- Method exit (with return value, if applicable)
- Thrown exceptions (checked and runtime)

By default, the interceptor will log all methods. By supplying parameters to the interceptor, you can control exactly which methods should be logged. The `include` and `exclude` parameter elements specify methods to be included (logged) and excluded (not logged). The `method` attribute is a *method pattern*, a string used to match methods based on name, number of parameters, or type of parameters; see the [MethodMatcher](#) class for more details.

A method which does not match any supplied pattern *will* be logged.

### 2.1.3. `hivemind.ShutdownCoordinator` Service

Service implementations that need to perform any special shutdown logic should implement the [RegistryShutdownListener](#) interface, and let the [hivemind.BuilderFactory](#) register them for notifications.

### 2.1.4. `hivemind.ThreadLocalStorage` Service

The [ThreadLocalStorage](#) service implements the [ThreadLocalStorage](#) interface. This service acts as a kind of Map for temporary data. The map is local to the current thread, and is cleared at the end of the transaction.

It is your responsibility to ensure that keys are unique, typically by prefixing them with a module id or package name.

## 2.2. Configurations

### 2.2.1. `hivemind.ApplicationDefaults` Configuration

The [ApplicationDefaults](#) configuration is used to set default values for substitution symbols. Application defaults override contributions to [hivemind.FactoryDefaults](#). The contribution format is the same `FactoryDefaults`:

```
<default symbol="..." value="..." />
```

### 2.2.2. `hivemind.EagerLoad` Configuration

The [EagerLoad](#) configuration allows services to be constructed when the Registry is first

initialized. Normally, HiveMind goes to great lengths to ensure that services are only constructed when they are first needed. Eager loading is appropriate during development (to ensure that services are configured properly), and some services that are event driven may need to be instantiated early, so that they may begin receiving event notifications even before their first service method is invoked.

Care should be taken when using services with the pooled or threaded service models to invoke cleanup the thread immediately after creating the Registry.

Contributions are as follows:

```
<load service-id="..." />
```

### 2.2.3. hivemind.FactoryDefaults Configuration

The [FactoryDefaults](#) configuration is used to set default values for substitution symbols. Contributions look like:

```
<default symbol="..." value="..." />
```

Values defined here can be overridden by making a contribution to [hivemind.ApplicationDefaults](#).

### 2.2.4. hivemind.ObjectProviders Configuration

The [ObjectProviders](#) configuration drives the object translator. Contributions define an object *provider* in terms of a prefix (such as `service`) and a service that implements the `ObjectProvider` interface.

Object *providers* exist to support *object references*. Object references are a way to contribute objects that may be references to services, or to other objects, or may even be created on the spot. This is often used with the [hivemind.BuilderFactory](#)'s `<set-object>` element.

An object reference consists of a *prefix* and a *locator* separated by a colon. The interpretation of the locator is different for each provider. The prefix determines which provider will be utilized to interpret the locator.

The contribution format defines the name and class for each service model:

```
<provider prefix="..." service-id="..." />
```

Prefixes must be unique.

The following default prefixes are available:

Prefix	Description	Example
--------	-------------	---------

bean	<p>The locator is a <a href="#">BeanFactory</a> locator, consisting of the id of a BeanFactory service, a colon, and an optional initializer for the bean.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p><b>Note:</b> Provided by the HiveMind library.</p> </div>	bean:ValidatorFactory:string,required
configuration	The locator is the id of a configuration.	configuration:MyConfiguration
instance	The locator is a fully qualified class name, which must have a public no arguments constructor.	instance:com.example.MyObject
service	The locator is the id of a service.	service:MyService
service-property	The locator provides a service id and a property name (provided by that service), seperated with a colon.	service-property:MyService:activeRequest

### 2.2.5. hivemind.ServiceModels Configuration

The [ServiceModels](#) configuration defines the available service models. Service models control the lifecycle of services: when they are created and when they are destroyed (often tied to the current thread's activity).

The contribution format defines the name and class for each service model:

```
<service-model name="..." class="..." />
```

An instance of the specified class will be instantiated. The class must implement the [ServiceModelFactory](#) interface (which creates an instance of the actual service model for a particular service extension point).

Names of service models must be unique; it is not possible to override the built-in service model factories.

### 2.2.6. hivemind.SymbolSources Configuration

The [SymbolSources](#) configuration is used to define new [SymbolSources](#) (providers of values

for substitution symbols).

Contributions are of the form:

```
<source name="..." before="..." after="..." class="..." service-id="..."/>
```

Sources are ordering based on the name, before and after elements. before and after may be comma-separated lists of other sources, may be the simple value \*, or may be omitted.

Only one of class and service-id attributes should be specified. The former is the complete name of a class (implementing the SymbolSource interface). The second is used to contribute a service (which must also implement the interface).

### **2.2.7. hivemind.Translators Configuration**

The [Translators](#) configuration defines the translators that may be used with XML conversion rules.

The contribution format defines the name and class for each service model:

```
<translator name="..." class="..."/>
```

An instance of the specified class will be instantiated. The class must implement the [Translator](#) interface. It should have a no-args and/or single String constructor.

Names of translators must be unique; it is not possible to override the existing service model translators. A single translator, class , is hard-coded into HiveMind, the others appear as ordinary contributions.

## **2.3. Ant Tasks**

### **2.3.1. ConstructRegistry Ant Task**

Reads some number of HiveMind module descriptors and assembles a single registry file from them. The output registry consists of a <registry> element which contains one <module> element for each module descriptor read. This registry is useful for generating documentation.

The registry XML is only updated if it does not exist, or if any of the module deployment descriptor is newer.

This task is implemented as [org.apache.hivemind.ant.ConstructRegistry](#).

### 2.3.1.1. Parameters

Attribute	Description	Required
output	The file to write the registry to.	Yes

### 2.3.1.2. Parameters specified as nested elements

#### descriptors

A path-like structure, used to identify which HiveMind module descriptors (hivemodule.xml) should be included.

Each path element should either be a module deployment descriptor, or be a JAR containing a deployment descriptor (in the META-INF folder).

### 2.3.1.3. Examples

Create target/registry.xml from all hivemodule.xml descriptors found inside the src directory.

```
<constructregistry output="target/registry.xml">
  <descriptors>
    <fileset dir="src">
      <include name="**/hivemodule.xml"/>
    </fileset>
  </descriptors>
</constructregistry>
```

## 2.3.2. ManifestClassPath Ant Task

Converts a classpath into a space-separated list of items used to set the Manifest Class-Path attribute.

This is highly useful when modules are packaged together inside an Enterprise Application Archive (EAR). Library modules may be deployed inside an EAR, but (in the current J2EE specs), there's no way for such modules to be added to the classpath in the deployment descriptor; instead, each JAR is expected to have a Manifest Class-Path attribute identifying the exactly list of JARs that should be in the classpath. This Task is used to generate that list.

This task is implemented as [org.apache.hivemind.ant.ManifestClassPath](http://org.apache.hivemind.ant.ManifestClassPath).

### 2.3.2.1. Parameters

Attribute	Description	Required
-----------	-------------	----------



property	The name of a property to set as a result of executing the task.	Yes
directory	If specified, then the directory attribute does two things: <ul style="list-style-type: none"><li>• It acts as a filter, limiting the results to just those elements that are within the directory</li><li>• It strips off the directory as a prefix (plus the separator), creating results that are relative to the directory.</li></ul>	No

### 2.3.2.2. Parameters specified as nested elements

#### classpath

A path-like structure, used to identify what the classpath should be.

### 2.3.2.3. Examples

Generate a list of JARs inside the `${target}` directory as relative paths and use it to set the Class-Path manifest attribute.

```
<manifestclasspath directory="${target}" property="manifest.class.path">
  <classpath refid="build.class.path"/>
</manifestclasspath>

<jar . . .>
  <manifest>
    <attribute name="Class-Path" value="${manifest.class.path}"/>
  </manifest>
</jar>
```

## 2.4. Reports

### 2.4.1.

### 2.4.2.

## 3. Module: hivemind.lib

## 3.1. Services

### 3.1.1. hivemind.lib.BeanFactoryBuilder Service

The [BeanFactoryBuilder](#) service is used to construct a [BeanFactory](#) instance. An BeanFactory will *vend out* instances of classes. A logical name is mapped to a particular Java class to be instantiated.

Client code can retrieve beans via the factory's `get()` method. Beans are retrieved using a *locator*, which consists of a name and an optional initializer separated by commas. The initializer is provided to the bean via an alternate constructor that takes a single string parameter. Initializers are used, typically, to initialize properties of the bean, but the actual implementation is internal to the bean class.

#### 3.1.1.1. Usage

The service takes a single parameter element:

```
<factory vend-class="..." configuration-id="..." default-cacheable="..." />
```

The `vend-class` attribute is the name of a class all vendable objects must be assignable to (as a class or interface). This is used to validate contributed bean definitions. By default it is `java.lang.Object`.

The `configuration-id` is the id of the companion configuration (used to define object classes).

The optional `default-cacheable` attribute sets the default for whether instantiated beans should be cached for reuse. By default this is true, which is appropriate for most use cases where the vendable objects are immutable.

#### 3.1.1.2. Configuration

Each BeanFactory service must have a configuration, into which beans are contributed:

```
<configuration-point id="..." schema-id="hivemind.lib.BeanFactoryContribution" />
```

Contributions into the configuration are used to specify the bean classes to instantiate, as:

```
<bean name="..." class="..." cacheable="..." />
```

`name` is a unique name used to reference an instance of the class.

`class` is the Java class to instantiate.

`cacheable` determines whether instances of the class are cacheable (that is, have immutable internal state and should be reused), or non-cacheable (presumably, because of mutable internal state).

### **3.1.2. `hivemind.lib.DefaultImplementationBuilder` Service**

The [DefaultImplementationBuilder](#) service is used to create default implementations of interfaces. As described in the [service interface JavaDoc](#), methods return null, 0 or false (depending on return type) and otherwise do nothing.

### **3.1.3. `hivemind.lib.EJBProxyFactory` Service**

The [EJBProxyFactory](#) service is used to construct a HiveMind service that delegates to an EJB stateless session bean. The EJB's remote interface is the service interface. When the first service method is invoked, the fabricated proxy will perform a JNDI lookup (using the [NameLookup](#) service), and invokes `create()` on the returned home interface.

The single service instance will be shared by all threads.

The service expects a single parameter element:

```
<construct home-interface="..." jndi-name="..." name-lookup-service="..." />
```

The `home-interface` attribute is the complete class name for the home interface, and is required.

The `jndi-name` attribute is the name of the EJB's home interface, also required.

The `name-lookup-service-id` attribute is optional and rarely used; it is an alternate service implementing the [NameLookup](#) interface to be used for JNDI lookups.

### **3.1.4. `hivemind.lib.NameLookup` Service**

The [NameLookup](#) service is a thin wrapper around JNDI lookup. It is used by the [EJBProxyFactory](#) service to locate EJBs.

The implementation makes use of three symbols (all of whose values default to null):

- `java.naming.factory.initial`
- `java.naming.factory.url.pkgs`
- `java.naming.provider.url`

By supplying overrides of these values, it is possible to configure how the [NameLookup](#)

service generates the InitialContext used for performing the JNDI lookup.

### 3.1.5. hivemind.lib.PlaceholderFactory Service

The [PlaceholderFactory](#) service is a service implementation factory that uses the [DefaultImplementationBuilder](#) service to create placeholder implementations for services. Placeholders do nothing at all.

### 3.1.6. hivemind.lib.PipelineFactory Service

The [PipelineFactory](#) services is used to construct a *pipeline* consisting of a series of filters. The filters implement an interface related to the service interface.

Each method of the service interface has a corresponding method in the filter interface with an identical signature, except that an additional parameter, whose type matches the *service interface* has been added.

For example, a service interface for transforming a string:

```
package mypackage;

public interface StringTransformService
{
    public String transform(String inputValue);
}
```

The corresponding filter interface:

```
package mypackage;

public interface StringTransformFilter
{
    public String transform(String inputValue, StringTransformService service);
}
```

The service parameter may appear at any point in the parameter list, though the convention of listing it last is recommended.

The filters in a pipeline are chained together as follows:

#### Pipeline Calling Sequence

The bridge objects implement the *service interface* (and are created dynamically at runtime). The *terminator* at the end also implements the service interface. This is an [object reference](#) (it can be an object or a service) if no terminator is specified, a [default implementation](#) is created and used. Only a single terminator is allowed.

A pipeline is always created in terms of a service and a configuration. The service defines the

service interface and identifies a configuration. The configuration conforms to the `hivemind.lib.Pipeline` schema and is used to specify filters and the terminator. Filters may be ordered much like [<interceptor>](#)s, using `before` and `after` attributes. This allows different modules to contribute filters into the service's pipeline.

### 3.1.6.1. Usage

The factory expects a single parameter element:

```
<create-pipeline filter-interface="..." configuration-id="..." terminator="..." />
```

The `filter-interface` attribute is the complete class name of the filter interface.

The `configuration-id` is the id of the companion configuration (used to define filters).

The optional `terminator` attribute is used to specify an [object reference](#). A terminator may also be contributed into the pipeline configuration.

### 3.1.6.2. Configuration

Each pipeline service must have a configuration, into which filters are contributed:

```
<configuration-point id="..." schema-id="hivemind.lib.Pipeline" />
```

### 3.1.6.3. Contributions

Contributions into the configuration are used to specify the filters and the terminator.

#### filter

```
<filter name="..." before="..." after="..." object="..." />
```

Contributes a filter. The optional `before` and `after` attributes are lists of the ids of other filters in the pipeline, used to set the ordering of the filters. They may be comma-separated lists of filter ids (or filter names), or simple `*` to indicate absolute positioning.

The `object` attribute is the filter object itself, an [object reference](#) to an object implementing the *filter interface*.

#### terminator

```
<terminator object="..." />
```

Specifies the terminator for the pipeline, as an [object reference](#) to an object implementing the *service interface*. Only a single terminator may be specified, and the terminator service

provided in the factory parameters takes precedence over a terminator in the configuration.

### 3.1.7. hivemind.lib.RemoteExceptionCoordinator Service

The [RemoteExceptionCoordinator](#) is used to propagate notifications of remote exceptions throughout the HiveMind repository. When any individual service encounters a remote exception, it notifies all listeners, who release all remote object proxies.

The service interface, [RemoteExceptionCoordinator](#), allows objects that implement the [RemoteExceptionListener](#) interface to be registered for notification, and includes a method for firing notifications.

### 3.1.8. hivemind.lib.ServicePropertyFactory Service

The [ServicePropertyFactory](#) exposes a property of a service as a new service. The property's type must be the same as (or assignable to) the service interface.

On each invocation of a service method, the property is re-acquired from the property source service, and the method reinvoked on the active value. This is useful when the value of the property can change at different times ... by using this factory, and not the service-property [object provider](#), your code will always access the current value.

This can be invaluable when a small number of services use the threaded or pooled service models. Other services can access information in those services transparently, without themselves having to be threaded or pooled.

A single parameter element is expected:

```
<construct service-id="..." property="..." />
```

Both attributes are required.

### 3.1.9. hivemind.lib.SpringLookupFactory Service

The [SpringLookupFactory](#) supports integration with the [Spring](#) framework, another open-source lightweight container. SpringLookupFactory is a service constructor that obtains a core service implementation from a Spring BeanFactory .

By default, the BeanFactory is obtained from the [DefaultSpringBeanFactoryHolder](#). Part of your application startup code requires that you start a Spring instance and inform the [DefaultSpringBeanFactoryHolder](#) about it.

The SpringLookupFactory expects exactly *one* parameter element:

```
<lookup-bean name="..." source-service-id="..." />
```

The name attribute is the name of the bean to look for inside the Spring BeanFactory.

The optional source-service-id attribute allows an alternate service to be used to obtain the Spring BeanFactory. The identified service must implement the [SpringBeanFactorySource](#) interface.

## 3.2. Reports

### 3.2.1.

### 3.2.2.

## 4. Example Code

### 4.1. Calculator

The calculator example demonstrates the most basic concepts of HiveMind; the difference between [<create-instance>](#) and [<invoke-factory>](#), the fact that services are, by default, created only as needed, and the ability of [hivemind.BuilderFactory](#) to automatically wire services together. It also demonstrates the behavior of the [hivemind.LoggingInterceptor](#).

After compiling the examples, you can use Ant to run them:

```
bash-2.05b$ ant run-calculator
Buildfile: build.xml
```

```
run-calculator:
  [java] Calculator [DEBUG] Creating SingletonProxy for service examples.Calculator
  [java] Inputs:      28.0 and 4.75
  [java] Calculator [DEBUG] Constructing core service implementation for service exa
  [java] Subtractor [DEBUG] Creating SingletonProxy for service examples.Subtractor
  [java] Calculator [DEBUG] Autowired service property subtractor to <SingletonProxy
  [java] Divider [DEBUG] Creating SingletonProxy for service examples.Divider
  [java] Calculator [DEBUG] Autowired service property divider to <SingletonProxy fo
  [java] Multiplier [DEBUG] Creating SingletonProxy for service examples.Multiplier
  [java] Calculator [DEBUG] Autowired service property multiplier to <SingletonProxy
  [java] Adder [DEBUG] Creating SingletonProxy for service examples.Adder
  [java] Calculator [DEBUG] Autowired service property adder to <SingletonProxy for
  [java] Calculator [DEBUG] Applying interceptor factory hivemind.LoggingInterceptor
  [java] Calculator [DEBUG] BEGIN add(28.0, 4.75)
  [java] Adder [DEBUG] Constructing core service implementation for service examples
  [java] Adder [DEBUG] Applying interceptor factory hivemind.LoggingInterceptor
  [java] Adder [DEBUG] BEGIN add(28.0, 4.75)
  [java] Adder [DEBUG] END add() [32.75]
  [java] Calculator [DEBUG] END add() [32.75]
```

```
[java] Add:      32.75
[java] Calculator [DEBUG] BEGIN subtract(28.0, 4.75)
[java] Subtracter [DEBUG] Constructing core service implementation for service example
[java] Subtracter [DEBUG] Applying interceptor factory hivemind.LoggingInterceptor
[java] Subtracter [DEBUG] BEGIN subtract(28.0, 4.75)
[java] Subtracter [DEBUG] END subtract() [23.25]
[java] Calculator [DEBUG] END subtract() [23.25]
[java] Subtract: 23.25
[java] Calculator [DEBUG] BEGIN multiply(28.0, 4.75)
[java] Multiplier [DEBUG] Constructing core service implementation for service example
[java] Multiplier [DEBUG] Applying interceptor factory hivemind.LoggingInterceptor
[java] Multiplier [DEBUG] BEGIN multiply(28.0, 4.75)
[java] Multiplier [DEBUG] END multiply() [133.0]
[java] Calculator [DEBUG] END multiply() [133.0]
[java] Multiply: 133.0
[java] Calculator [DEBUG] BEGIN divide(28.0, 4.75)
[java] Divider [DEBUG] Constructing core service implementation for service example
[java] Divider [DEBUG] Applying interceptor factory hivemind.LoggingInterceptor
[java] Divider [DEBUG] BEGIN divide(28.0, 4.75)
[java] Divider [DEBUG] END divide() [5.894736842105263]
[java] Calculator [DEBUG] END divide() [5.894736842105263]
[java] Divide:    5.894736842105263
```

```
BUILD SUCCESSFUL
Total time: 3 seconds
```

The logging configuration enables logging for the hivemind logger; that and the logging interceptors produces quite a bit of output. You can see that a *proxy* is created for services initially, and that the "core service implementation" for the service is created later ... the core service implementation consists of an instance of the service's POJO class, wrapped with any interceptors (the logging interceptor, in this case).

The Registry is built from the following module deployment descriptor:

```
<?xml version="1.0"?>
<module id="examples" version="1.0.0">
  <service-point id="Adder" interface="org.apache.hivemind.examples.Adder">
    <create-instance class="org.apache.hivemind.examples.impl.AdderImpl"/>
    <interceptor service-id="hivemind.LoggingInterceptor"/>
  </service-point>
  <service-point id="Subtracter" interface="org.apache.hivemind.examples.Subtracter">
    <create-instance class="org.apache.hivemind.examples.impl.SubtracterImpl"/>
    <interceptor service-id="hivemind.LoggingInterceptor"/>
  </service-point>
  <service-point id="Multiplier" interface="org.apache.hivemind.examples.Multiplier">
    <create-instance class="org.apache.hivemind.examples.impl.MultiplierImpl"/>
    <interceptor service-id="hivemind.LoggingInterceptor"/>
  </service-point>
  <service-point id="Divider" interface="org.apache.hivemind.examples.Divider">
    <create-instance class="org.apache.hivemind.examples.impl.DividerImpl"/>
    <interceptor service-id="hivemind.LoggingInterceptor"/>
  </service-point>
</module>
```



```
<service-point id="Calculator" interface="org.apache.hivemind.examples.Calculator">
  <invoke-factory>
    <construct class="org.apache.hivemind.examples.impl.CalculatorImpl"/>
  </invoke-factory>
  <interceptor service-id="hivemind.LoggingInterceptor"/>
</service-point>
</module>
```

The service-point for the Calculator service is very simple ... as the comment indicates, the BuilderFactory is capable of locating the other services (Adder, Subtractor, etc.) by their *interface*, rather than requiring `set-service` elements to connect properties to services (using the target service's ids). These *properties* of the Calculator *implementation* are *autowired* to the matching services. Autowiring works only because just a single service within the *entire* Registry implements the specific interface. You would see errors if no service implemented the interface, or if more than one did.

## 4.2. Panorama Startup

Panorama is a disguised version of [WebCT](#)'s **Vista** application. Vista is a truly massive web application, consisting of thousands of Java classes and JSPs and hundreds of EJBs. Vista is organized as a large number of somewhat interrelated *tools* with an underlying substrate of *services*. In fact, HiveMind was originally created to manage the complexity of Vista.

### Note:

The reality is that Vista, a commercial project, has continued with an older version of HiveMind. Panorama is based on original code in Vista, but has been altered to take advantage of many features available in more recent versions of HiveMind. Keeping the names separate keeps us honest about the differences between a product actually in production (Vista) versus an idealized version used for demonstration and tutorial purposes (Panorama).

With all these interrelated tools and services, the simple act of starting up the application was complex. Many tools and services have *startup operations*, things that need to occur when the application first starts up within the application server. For example, the help service reads and caches help text stored within the database. The mail service creates periodic jobs to perform database garbage collection of deleted mail items. All told, Vista had over 40 different tasks to perform at startup ... many with subtle dependencies (such as the mail tool needing the job scheduler service to be up and running).

The *legacy* version of Vista startup consisted of a WebLogic startup class that invoked a central stateless session EJB. The startup EJB was responsible for performing all 40+ startup tasks ... typically by invoking a public static method of a class related to the tool.

This was problematic for several reasons. It created a dependency on WebLogic to manage startup (really, a minor consideration, but one nonetheless). More importantly, it created an unnecessary binding between the startup EJB and all the other code in all the other tools.

These unwanted dependencies created ripple effects throughout the code base that impacted refactored efforts, and caused deployment problems that complicated the build (requiring the duplication of many common classes inside the startup EJB's JAR, to resolve runtime classloader dependencies).

**Note:**

It's all about class loaders. The class loader that loaded the startup EJB didn't have visibility to the contents of the other EJB JARs deployed within the Vista EAR. To satisfy WebLogic's ejbc command (EJB JAR packaging tool), and to successfully locate the classes at runtime, it was necessary to duplicate many classes from the other EJB JARs into the startup EJB JAR. With HiveMind, this issue goes away, since the module deployment descriptors store the class *name*, and the *servlet thread's context class loader* is used to resolve that name ... and it has visibility to all the classes in all the EJB JARs.

#### 4.2.1. Enter HiveMind

HiveMind's ultimate purpose was to simplify all aspects of Vista development and create a simpler, faster, more robust development environment. The first step on this journey, a trial step, was to rationalize the startup process.

Each startup task would be given a unique id, a title and a set of *dependencies* (on other tasks). How the task actually operated was left quite abstract ... with careful support for supporting the existing legacy approach (public static methods). What would change would be how these tasks were executed.

The advantage of HiveMind is that each *module* can contribute as many or as few startup tasks as necessary into the Startup configuration point as needed. This allows the startup logic to be properly *encapsulated* in the module. The startup logic can be easily changed without affecting other modules, and without having to change any single contentious resource (such as the legacy approach's startup EJB).

#### 4.2.2. Startup task schema

The schema for startup tasks contributions must support the explicit ordering of execution based on dependencies. With HiveMind, there's no telling in what order modules will be processed, and so no telling in what order contributions will appear within a configuration point ... so it is necessary to make ordering explicit by giving each task a unique id, and listing dependencies (the ids of tasks that must precede, or must follow, any single task).

Special consideration was given to supporting legacy startup code in the tools and services; code that stays in the form of a public static method. As HiveMind is adopted, these static methods will go away, and be replaced with either HiveMind services, or simple objects. In the very long term, much of this startup logic will become unnecessary, as more of the system will be implemented using HiveMind services, which will lazily initialize just as needed.

The schema definition (with descriptions removed, for compactness) follows:

```
<schema id="Tasks">
  <element name="task">
    <attribute name="title" required="true"/>
    <attribute name="id" required="true"/>
    <attribute name="before"/>
    <attribute name="after"/>
    <attribute name="executable" required="true" translator="object"/>

    <conversion class="com.panorama.startup.impl.Task"/>
  </element>

  <element name="static-task">
    <attribute name="title" required="true"/>
    <attribute name="id" required="true"/>
    <attribute name="before"/>
    <attribute name="after"/>
    <attribute name="class" translator="class" required="true"/>
    <attribute name="method"/>

    <rules>
      <create-object class="com.panorama.startup.impl.Task"/>
      <invoke-parent method="addElement"/>

      <read-attribute attribute="id" property="id"/>
      <read-attribute attribute="title" property="title"/>
      <read-attribute attribute="before" property="before"/>
      <read-attribute attribute="after" property="after"/>

      <create-object class="com.panorama.startup.impl.ExecuteStatic"/>
      <invoke-parent method="setExecutable"/>

      <read-attribute attribute="class" property="targetClass"/>
      <read-attribute attribute="method" property="methodName"/>
    </rules>
  </element>
</schema>
```

**Note:**

For more details, see [the HiveDoc for the Tasks schema](#).

This schema supports contributions in two formats. The first format allows an arbitrary object or service to be contributed:

```
<task id="mail" title="Mail" executable="service:MailStartup"/>
```

The executable attribute is converted into an object or service; here the `service:` prefix indicates that the rest of the string, `MailStartup`, is a service id (other prefixes are defined by the [hivemind.ObjectProviders](#) configuration). If this task has dependencies, the

before and after attributes can be specified as well.

To support legacy code, a second option, `static-task`, is provided:

```
<static-task id="discussions" title="Discussions" after="mail" class="com.panorama.disc
```

The `static-task` element duplicates the `id`, `title`, `before` and `after` attributes, but replaces `executable` with `class` (the name of the class containing the method) and `method` (the name of the method to invoke, defaulting to "init").

### 4.2.3. Startup Service

The schema just defines what contributions *look like* and how they are converted to objects; we need to define a Startup configuration point using the schema, and a Startup service that uses the configuration point.

```
<configuration-point id="Startup" schema-id="Tasks"/>

<service-point id="Startup" interface="java.lang Runnable">
  <invoke-factory>
    <construct class="com.panorama.startup.impl.TaskExecutor">
      <set-configuration property="tasks" configuration-id="Startup"/>
    </construct>
  </invoke-factory>
</service-point>

<contribution id="hivemind.Startup">
  <startup object="service:Startup"/>
</contribution>
```

The `hivemind.Startup` configuration point is used to ensure that the Panorama Startup service is executed when the Registry itself is constructed.

### 4.2.4. Implementation

All that remains is the implementations of the service and task classes.

#### 4.2.4.1. Executable.java

```
package com.panorama.startup;

/**
 * Much like {@link java.lang Runnable}, but allows the caller
 * to handle any exceptions thrown.
 *
 * @author Howard Lewis Ship
 */
public interface Executable
{
```

```
    public void execute() throws Exception;
}
```

The Executable interface is implemented by tasks, and by services or other objects that need to be executed. It throws `Exception` so that exception catching and reporting can be centralized inside the Startup service.

#### **4.2.4.2. Task.java**

```
package com.panorama.startup.impl;

import org.apache.hivemind.impl.BaseLocatable;
import com.panorama.startup.Executable;

/**
 * An operation that may be executed. A Task exists to wrap
 * an {@link com.panorama.startup.Executable} object with
 * a title and ordering information (id, after, before).
 *
 * @author Howard Lewis Ship
 */
public class Task extends BaseLocatable implements Executable
{
    private String _id;
    private String _title;
    private String _after;
    private String _before;
    private Executable _executable;

    public String getBefore()
    {
        return _before;
    }

    public String getId()
    {
        return _id;
    }

    public String getAfter()
    {
        return _after;
    }

    public String getTitle()
    {
        return _title;
    }

    public void setExecutable(Executable executable)
    {
        _executable = executable;
    }
}
```

```

    }

    public void setBefore(String string)
    {
        _before = string;
    }

    public void setId(String string)
    {
        _id = string;
    }

    public void setAfter(String string)
    {
        _after = string;
    }

    public void setTitle(String string)
    {
        _title = string;
    }

    /**
     * Delegates to the {@link #setExecutable(Executable) executable} object.
     */
    public void execute() throws Exception
    {
        _executable.execute();
    }
}

```

The Task class is a wrapper around an Executable object; whether that's a service, some arbitrary object, or a StaticTask.

#### 4.2.4.3. ExecuteStatic.java

```

package com.panorama.startup.impl;

import java.lang.reflect.Method;

import com.panorama.startup.Executable;

/**
 * Used to access the legacy startup code that is in the form
 * of a public static method (usually init()) on some
 * class.
 *
 * @author Howard Lewis Ship
 */
public class ExecuteStatic implements Executable
{
    private String _methodName = "init";
    private Class _targetClass;
}

```

```
public void execute() throws Exception
{
    Method m = _targetClass.getMethod(_methodName, null);

    m.invoke(null, null);
}

/**
 * Sets the name of the method to invoke; if not set, the default is <code>init</code>
 * The target class must have a public static method with that name taking no
 * parameters.
 */
public void setMethodName(String string)
{
    _methodName = string;
}

/**
 * Sets the class to invoke the method on.
 */
public void setTargetClass(Class targetClass)
{
    _targetClass = targetClass;
}
}
```

ExecuteStatic uses Java reflection to invoke a public static method of a particular class.

#### **4.2.4.4. TaskExecutor.java**

```
package com.panorama.startup.impl;

import java.util.Iterator;
import java.util.List;

import org.apache.commons.logging.Log;
import org.apache.hivemind.ErrorHandler;
import org.apache.hivemind.Messages;
import org.apache.hivemind.order.Orderer;

/**
 * A service that executes a series of {@link com.panorama.startup.impl.Task}s. Tasks h
 * an ordering based on pre- and post-requisites.
 *
 * @author Howard Lewis Ship
 */
public class TaskExecutor implements Runnable
{
    private ErrorHandler _errorHandler;
    private Log _log;
    private List _tasks;
    private Messages _messages;
```

```
/**
 * Orders the {@link #setTasks(List) tasks} into an execution order, and executes
 * each in turn. Logs the elapsed time, number of tasks, and the number of failure
 */
public void run()
{
    long startTime = System.currentTimeMillis();

    Orderer orderer = new Orderer(_log, _errorHandler, task());

    Iterator i = _tasks.iterator();
    while (i.hasNext())
    {
        Task t = (Task) i.next();

        orderer.add(t, t.getId(), t.getAfter(), t.getBefore());
    }

    List orderedTasks = orderer.getOrderedObjects();

    int failures = 0;

    i = orderedTasks.iterator();
    while (i.hasNext())
    {
        Task t = (Task) i.next();

        if (!execute(t))
            failures++;
    }

    long elapsedTime = System.currentTimeMillis() - startTime;

    if (failures == 0)
        _log.info(success(orderedTasks.size(), elapsedTime));
    else
        _log.info(failure(failures, orderedTasks.size(), elapsedTime));
}

/**
 * Execute a single task.
 *
 * @return true on success, false on failure
 */
private boolean execute(Task t)
{
    _log.info(executingTask(t));

    try
    {
        t.execute();

        return true;
    }
}
```



```
        catch (Exception ex)
        {
            _errorHandler.error(_log, exceptionInTask(t, ex), t.getLocation(), ex);

            return false;
        }
    }

    private String task()
    {
        return _messages.getMessage("task");
    }

    private String executingTask(Task t)
    {
        return _messages.format("executing-task", t.getTitle());
    }

    private String exceptionInTask(Task t, Throwable cause)
    {
        return _messages.format("exception-in-task", t.getTitle(), cause);
    }

    private String success(int count, long elapsedTimeMillis)
    {
        return _messages.format("success", new Integer(count), new Long(elapsedTimeMill
    }

    private String failure(int failureCount, int totalCount, long elapsedTimeMillis)
    {
        return _messages.format(
            "failure",
            new Integer(failureCount),
            new Integer(totalCount),
            new Long(elapsedTimeMillis));
    }

    public void setErrorHandler(ErrorHandler handler)
    {
        _errorHandler = handler;
    }

    public void setLog(Log log)
    {
        _log = log;
    }

    public void setMessages(Messages messages)
    {
        _messages = messages;
    }

    public void setTasks(List list)
    {
```

```

        _tasks = list;
    }
}

```

This class is where it all comes together; it is the core service implementation for the `panorama.startup.Startup` service. It is constructed by the [hivemind.BuilderFactory](#), which autowires the `errorHandler`, `log` and `messages` properties, as well as the `tasks` property (which is explicitly set in the module deployment descriptor).

Most of the `run()` method is concerned with ordering the contributed tasks into execution order and reporting the results.

#### 4.2.5. Unit Testing

Unit testing in HiveMind is accomplished by *acting like the container*; that is, your code is responsible for instantiating the core service implementation and setting its properties. In many cases, you will set the properties to mock objects ... HiveMind uses [EasyMock](#) extensively, and provides a base class, `HiveMindTestCase`, that contains much support for creating Mock controls and objects.

##### 4.2.5.1. TestTaskExecutor.java

```

package com.panorama.startup.impl;

import java.util.ArrayList;
import java.util.Collections;
import java.util.List;
import java.util.Locale;

import org.apache.commons.logging.Log;
import org.apache.hivemind.ApplicationRuntimeException;
import org.apache.hivemind.ErrorHandler;
import org.apache.hivemind.Messages;
import org.apache.hivemind.Resource;
import org.apache.hivemind.impl.MessagesImpl;
import org.apache.hivemind.test.ExceptionAwareArgumentsMatcher;
import org.apache.hivemind.test.HiveMindTestCase;
import org.apache.hivemind.test.RegexpArgumentsMatcher;
import org.apache.hivemind.util.FileResource;
import org.easymock.MockControl;

import com.panorama.startup.Executable;

/**
 * Tests for the {@link com.panorama.startup.impl.TaskExecutor} service.
 *
 * @author Howard Lewis Ship
 */

```

```
public class TestTaskExecutor extends HiveMindTestCase
{
    private static List _tokens = new ArrayList();

    protected void setUp()
    {
        _tokens.clear();
    }

    protected void tearDown()
    {
        _tokens.clear();
    }

    public static void addToken(String token)
    {
        _tokens.add(token);
    }

    public Messages getMessages()
    {
        . . .
    }

    public void testSuccess()
    {
        ExecutableFixture f1 = new ExecutableFixture("f1");

        Task t1 = new Task();

        t1.setExecutable(f1);
        t1.setId("first");
        t1.setAfter("second");
        t1.setTitle("Fixture #1");

        ExecutableFixture f2 = new ExecutableFixture("f2");

        Task t2 = new Task();
        t2.setExecutable(f2);
        t2.setId("second");
        t2.setTitle("Fixture #2");

        List tasks = new ArrayList();
        tasks.add(t1);
        tasks.add(t2);

        MockControl logControl = newControl(Log.class);
        Log log = (Log) logControl.getMock();

        TaskExecutor e = new TaskExecutor();

        ErrorHandler errorHandler = (ErrorHandler) newMock(ErrorHandler.class);
        e.setErrorHandler(errorHandler);
    }
}
```

```

        e.setLog(log);
        e.setMessages(getMessages());
        e.setTasks(tasks);

        // Note the ordering; explicitly set, to check that ordering does
        // take place.
        log.info("Executing task Fixture #2.");
        log.info("Executing task Fixture #1.");
        log.info("Executed 2 tasks \\(in \\d+ milliseconds\\)\\.");
        logControl.setMatcher(new RegexpArgumentsMatcher());

        replayControls();

        e.run();

        assertListsEqual(new String[] { "f2", "f1" }, _tokens);

        verifyControls();
    }
}

```

In this listing (which is a paired down version of the real class), you can see how mock objects, including EasyMock objects, are used. The ExecutableFixture classes will invoke the `addToken()` method; the point is to provide, in the tasks List, those fixtures wrapped in Task objects and see that they are invoked in the correct order.

We create a Mock Log object, and check that the correct messages are logged in the correct order. Once we have set the expectations for all the EasyMock controls, we invoke `replayControls()` and continue with our test. The `verifyControls()` method ensures that all mock objects have had all expected methods invoked on them.

That's just *unit* testing; you always want to supplement that with *integration* testing ... to ensure, at the very least, that your schema is valid, the conversion rules work, and the contributions are correct. However, as the [code coverage report](#) shows, you can reach very high levels of code coverage (and code *confidence*) using unit tests.

### 4.3. Creating a Logging Interceptor

One of the most powerful features of HiveMind is the ability to create *interceptors* for services. Interceptors provide additional behavior to a service, often a *cross-cutting concern* such as logging or transaction management. Interceptors can be thought of as "aspect oriented programming lite".

This example shows how easy it can be to create an interceptor; it creates a simplified version of the standard [hivemind.LoggingInterceptor](#).

The *real* logging interceptor uses the [Javassist](#) bytecode enhancement framework to create a

new class at runtime. This has some minor advantages in terms of runtime performance, but is much more complicated to implement and test than this example, which uses [JDK Dynamic Proxies](#).

#### 4.3.1. The Interceptor Factory

Interceptors are created by interceptor factories, which are themselves HiveMind services. Interceptor factories implement the [ServiceInterceptorFactory](#) interface.

Our implementation is very simple:

```
package org.apache.hivemind.examples.impl;

import java.lang.reflect.InvocationHandler;
import java.lang.reflect.Proxy;
import java.util.List;

import org.apache.commons.logging.Log;
import org.apache.hivemind.InterceptorStack;
import org.apache.hivemind.ServiceInterceptorFactory;
import org.apache.hivemind.internal.Module;

public class ProxyLoggingInterceptorFactory implements ServiceInterceptorFactory
{
    public void createInterceptor(InterceptorStack stack, Module invokingModule, List p
    {
        Log log = stack.getServiceLog();

        InvocationHandler handler = new ProxyLoggingInvocationHandler(log, stack.peek()

        Object interceptor =
            Proxy.newProxyInstance(
                invokingModule.getClassResolver().getClassLoader(),
                new Class[] { stack.getServiceInterface() },
                handler);

        stack.push(interceptor);
    }
}
```

The `createInterceptor()` method is passed the [InterceptorStack](#), the [Module](#) of the invoking module (the module containing the service being created), and any parameters passed to the interceptor (from inside the [<interceptor>](#) element). This example does not make use of parameters, but the real logging interceptor uses parameters to control which methods are, and are not, logged.

An interceptor's job is to `peek()` at the top object on the stack and create a new object, wrapped around the top object, that provides new behavior. The top object on the stack may be the core service implementation, or it may be another interceptor ... all that's known for

sure is that it implements the service interface defined by the [<service-point>](#).

The interceptor in this case is a dynamic proxy, provided by `Proxy.newProxyInstance()`. The key here is the *invocation handler*, and object (described shortly) that is notified any time a method on the interceptor proxy is invoked.

Once the interceptor is created, it is pushed onto the stack. More interceptors may build upon it, adding yet more behavior.

In HiveMind, a single `Log` instance is used when constructing a service as well as by any interceptors created for the service. In other words, by enabling logging for a particular service id, you will see log events for every aspect of the construction of that particular service. If you add a logging interceptor, you'll also see method invocations. To ensure that logging takes place using the single logging instance, neither the class nor the interceptor factory is responsible for creating the logging instance ... that's the responsibility of HiveMind. The logging instance to use is provided by the `getServiceLog()` method of the [InterceptorStack](#) instance provided to the interceptor factory.

#### 4.3.2. Invocation Handler

The invocation handler is where the intercepting really takes place; it is invoked every time a method of the proxy object is invoked and has a chance to add behavior before, and after (or even instead of!) invoking a method on the next object in the stack. What is the "next object"? It's the next object in the interceptor stack, and may be another interceptor instance, or may be the core service implementation.

```
package org.apache.hivemind.examples.impl;

import java.lang.reflect.InvocationHandler;
import java.lang.reflect.InvocationTargetException;
import java.lang.reflect.Method;

import org.apache.commons.logging.Log;
import org.apache.hivemind.service.impl.LoggingUtils;

public class ProxyLoggingInvocationHandler implements InvocationHandler
{
    private Log _log;
    private Object _inner;

    public ProxyLoggingInvocationHandler(Log log, Object inner)
    {
        _log = log;
        _inner = inner;
    }

    public Object invoke(Object proxy, Method method, Object[] args) throws Throwable
    {
```

```
boolean debug = _log.isDebugEnabled();

if (debug)
    LoggingUtils.entry(_log, method.getName(), args);

try
{
    Object result = method.invoke(_inner, args);

    if (debug)
    {
        if (method.getReturnType() == void.class)
            LoggingUtils(voidExit(_log, method.getName()));
        else
            LoggingUtils.exit(_log, method.getName(), result);
    }

    return result;
}
catch (InvocationTargetException ex)
{
    Throwable targetException = ex.getTargetException();

    if (debug)
        LoggingUtils.exception(_log, method.getName(), targetException);

    throw targetException;
}
}
```

The `invoke()` method is the key. Using the remembered `Log` instance, and the remembered inner object (the next inner object on the interceptor stack ... the object that was `peek()`-ed). The code for actually generating the logging output is inside static methods of the `LoggingUtils` utility class -- in this way the output from this interceptor is identical to the output when using [hivemind.LoggingInterceptor](#).

The `invoke()` method is invoked for all methods that can be invoked on the proxy ... this includes the methods of the service interface, but also includes `java.lang.Object` methods such as `hashCode()` or `toString()`.

**Note:**

The [hivemind.LoggingInterceptor](#) will typically add its own implementation of `toString()`, to assist in debugging (it clearly identifies itself as an interceptor object, and identifies the service id and service interface). This proxy-based implementation does not, so invoking `toString()` on the proxy will end up invoking the method on the next object.

### 4.3.3. Declaring the interceptor factory

Like any other service, an service interceptor factory must appear inside a HiveMind module

deployment descriptor:

```
<service-point id="ProxyLoggingInterceptor" interface="org.apache.hivemind.ServiceInter
  <create-instance class="org.apache.hivemind.examples.impl.ProxyLoggingInterceptorFact
</service-point>
```

#### 4.3.4. Using the interceptor

Using the interceptor is the same as using any other interceptor; the [<interceptor>](#) element simply has to point at the correct service:

```
<service-point id="Target" interface="org.apache.hivemind.examples.TargetService">
  <create-instance class="org.apache.hivemind.examples.impl.TargetServiceImpl"/>

  <interceptor service-id="ProxyLoggingInterceptor"/>
</service-point>
```

The `TargetService` interface defines three methods used to demonstrate the logging interceptor:

```
package org.apache.hivemind.examples;

import java.util.List;

public interface TargetService
{
    public void voidMethod(String string);

    public List buildList(String string, int count);

    public void exceptionThrower();
}
```

The implementation class is equally inspiring:

```
package org.apache.hivemind.examples.impl;

import java.util.ArrayList;
import java.util.List;

import org.apache.hivemind.ApplicationRuntimeException;
import org.apache.hivemind.examples.TargetService;

public class TargetServiceImpl implements TargetService
{
    public void voidMethod(String string)
    {
    }
}
```



```
public List buildList(String string, int count)
{
    List result = new ArrayList();

    for (int i = 0; i < count; i++)
        result.add(string);

    return result;
}

public void exceptionThrower()
{
    throw new ApplicationRuntimeException("Some application exception.");
}
}
```

### 4.3.5. Running the examples

From the examples directory, run `ant compile`, then run `ant -emacs run-logging`:

```
bash-2.05b$ ant -emacs run-logging
Buildfile: build.xml

run-logging:
Target [DEBUG] Creating SingletonProxy for service examples.Target

*** Void method (no return value):

Target [DEBUG] Constructing core service implementation for service examples.Target
Target [DEBUG] Applying interceptor factory examples.ProxyLoggingInterceptor
ProxyLoggingInterceptor [DEBUG] Creating SingletonProxy for service examples.ProxyLoggi
ProxyLoggingInterceptor [DEBUG] Constructing core service implementation for service ex
Target [DEBUG] BEGIN voidMethod(Hello)
Target [DEBUG] END voidMethod()

*** Ordinary method (returns a List):

Target [DEBUG] BEGIN buildList(HiveMind, 4)
Target [DEBUG] END buildList() [[HiveMind, HiveMind, HiveMind, HiveMind]]

*** Exception method (throws an exception):

Target [DEBUG] BEGIN exceptionThrower()
Target [DEBUG] EXCEPTION exceptionThrower() -- org.apache.hivemind.ApplicationRuntimeEx
org.apache.hivemind.ApplicationRuntimeException: Some application exception.
    at org.apache.hivemind.examples.impl.TargetServiceImpl.exceptionThrower(TargetS
    at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
    at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:39)
    at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl
    at java.lang.reflect.Method.invoke(Method.java:324)
    at org.apache.hivemind.examples.impl.ProxyLoggingInvocationHandler.invoke(Proxy
    at $Proxy0.exceptionThrower(Unknown Source)
```

```
at $SingletonProxy_fe67f7e0ae_12.exceptionThrower($SingletonProxy_fe67f7e0ae_12
at org.apache.hivemind.examples.LoggingMain.main(LoggingMain.java:27)
at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:39)
at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl
at java.lang.reflect.Method.invoke(Method.java:324)
at org.apache.tools.ant.taskdefs.ExecuteJava.run(ExecuteJava.java:193)
at org.apache.tools.ant.taskdefs.ExecuteJava.execute(ExecuteJava.java:130)
at org.apache.tools.ant.taskdefs.Java.run(Java.java:705)
at org.apache.tools.ant.taskdefs.Java.executeJava(Java.java:177)
at org.apache.tools.ant.taskdefs.Java.execute(Java.java:83)
at org.apache.tools.ant.UnknownElement.execute(UnknownElement.java:275)
at org.apache.tools.ant.Task.perform(Task.java:364)
at org.apache.tools.ant.Target.execute(Target.java:341)
at org.apache.tools.ant.Target.performTasks(Target.java:369)
at org.apache.tools.ant.Project.executeTarget(Project.java:1214)
at org.apache.tools.ant.Project.executeTargets(Project.java:1062)
at org.apache.tools.ant.Main.runBuild(Main.java:673)
at org.apache.tools.ant.Main.startAnt(Main.java:188)
at org.apache.tools.ant.launch.Launcher.run(Launcher.java:196)
at org.apache.tools.ant.launch.Launcher.main(Launcher.java:55)
```

```
BUILD SUCCESSFUL
Total time: 3 seconds
```

The `log4j.properties` file for the examples has enabled debug logging for the entire module; thus we see some output about the construction of the `ProxyLoggingInterceptor` service as it is employed to construct the interceptor for the `Target` service.

### **4.3.6. Conclusion**

Implementing a basic interceptor using HiveMind is very simple when using JDK Dynamic Proxies. You can easily provide code that slips right into the calling sequence for the methods of your services with surprisingly little code. In addition, the APIs do not force you to use any single approach; you can use JDK proxies as here, use Javassist, or use any approach that works for you. And because interceptor factories are themselves HiveMind services, you have access to the entire HiveMind environment to implement your interceptor factories.

## **4.4. Reports**

### **4.4.1.**

### **4.4.2.**

**4.4.3.**

**5. Other Resources**

**6. Complete Site**

**7. Related Projects**